

VENT_243

VENT_243

NEVADA BUREAU OF MINES AND GEOLOGY

BULLETIN 91

THERMAL WATERS OF NEVADA

**LARRY J. GARSIDE
JOHN H. SCHILLING**

Descriptions of Nevada's thermal waters in springs, wells, and mine workings: locations, geology, temperatures, flow rates, water chemistry, well depths, drilling and other exploration activities, and past and present uses.



**MACKAY SCHOOL OF MINES
UNIVERSITY OF NEVADA • RENO
1979**

ESMERALDA COUNTY (continued)

Travertine deposit [88]

A mound of calcareous spring travertine occurs in C NW/4 S5,T1N,R43E, near the south end of the Klondyke Hills. There are no known hot springs in the vicinity. The mound is about 600 feet in diameter, and occurs in an area of Tertiary welded tuffs and Paleozoic limestones.

EUREKA COUNTY


Beowawe Geysers [94]

The geothermal area at Beowawe Geysers has the highest reported subsurface temperatures in Eureka County, and, with the Brady's Hot Spring area in Churchill County, has the highest steam-well temperatures in Nevada. It is one of the most drilled geothermal areas in the State, and has been actively investigated by several energy companies over the past 15 years.


The surface geothermal activity at the Beowawe Geysers area is mainly confined to S8,17,18,T31N,R48E. This area

is mainly in Eureka County, although S18 is in Lander County. For simplicity, this description is included in Eureka County. The Geysers is in southwestern Whirlwind Valley, about 6 miles west of the small community of Beowawe.

The hot springs, geysers, and fumaroles have temperatures up to 202° to 204°F, and in 1932 several geysers were reported to erupt to heights of several feet (Nolan and Anderson, 1934). One geyser reportedly played to a height of 3 feet and another to 12 feet. Drilling of geothermal exploration wells on the main sinter terrace in the early 1960's resulted in the disruption of natural geyser activity there, but geysers on the valley floor to the west of the terrace were considerably more thermally active in 1968 than in 1932 (Rinehart, 1968). These geysers erupted to heights of 3 to 6 feet. Vandals blew the caps from four steam wells on the main terrace sometime prior to 1972, and one of these released steam and water in rather large volumes. One of the notable effects of this release of fluid and possibly the original drilling was the cessation of geyser activity (Hose and Taylor, 1974). The "best guess"



Steam wells on the sinter terrace at Beowawe Geysers in 1977 (photo by Dennis Trexler).



Steam well at Beowawe Geysers, Eureka County (photo by Dennis Trexler).




FIGURE 24. Geologic map of Beowawe Geysers, Eureka and Lander Counties (from Oesterling, 1962).

EUREKA COUNTY (continued)

estimates of thermal reservoir temperatures are approximately 385°F for a sample from a spring, and 440° to 460°F for a sample from a steam well (Mariner and others, 1974). Since temperatures of over 400°F are reported from shallow depths, the higher estimates seem likely to be realized.

The most conspicuous feature of the Beowawe Geysers is an enormous, symmetrical spring-sinter terrace which stands some 250 feet high. The top of the terrace, which measures 100 feet wide and 2,800 feet long, is remarkably level (Oesterling, 1962). The flowing springs and geothermal wells are located along a narrow band of older sinter which is present between the main terrace and outcrops of Tertiary andesite to the south (Hose and Taylor, 1974, fig. 4). The siliceous sinter is almost entirely made up of opal, and it is presently forming around certain pools (Nolan and Anderson, 1934). The sinter reportedly contains 300 ppm tungsten and high beryllium (R. Erickson, personal communication, 1970); tungsten is also high in the geothermal fluids (Wollenberg and others, 1975).

The Geysers are located at the south edge of Whirlwind Valley along a major fault zone which is at least 35, and possibly up to 70, miles in length. The zone extends from the central Shoshone Range along southern Whirlwind Valley and then across the center of the Tuscarora Mountains (Stewart and Carlson, 1976b). The east-northeast trending faults mapped by Oesterling (fig. 24) are part of this zone. Beowawe Geysers are located at the intersection of this zone with several northwest-trending faults and lineaments (Oesterling, 1962; Trexler, 1977). Recent movement is believed to have taken place on faults which cut the sinter terrace (Oesterling, 1962). The surface thermal activity is mainly confined to a 3,000-foot segment of the Terrace Fault and a 1,300-foot segment of the Horst Fault (fig. 24). The rocks exposed along the ridge called Malpais to the south of the geothermal area are predominantly basalts and andesites. A few outcrops of the underlying Ordovician Vinini Formation are also present, and this unit was encountered at depth in some of the drill holes (fig. 25).

Twelve exploratory geothermal wells were drilled in S17, T31N, R48E at Beowawe Geysers from 1959 through 1965. These wells were drilled by Magma Power Co., Vulcan Thermal Power Co., and Sierra Pacific Power Co. The deepest well drilled during this period was 2,052 feet; several of the wells had temperatures of 407° to 414°F at depths of 700 to 800 feet. Since 1974, three more wells have been drilled, two of them to approximately 5,500 feet, and a third to 9,563 feet. The Magma Energy, Inc. Batz No. 1 was drilled to 5,447 feet in S17, T31N, R48E, near the previous wells. Two wells, the Chevron-American Thermal Resources Ginn No. 1-13 and the Chevron U.S.A., Inc. Rossi No. 21-19, were drilled in an area approximately 1.5 miles to the southwest of the Geysers. These wells reportedly encountered high-temperature fluids in faulted zones near the bottom of both wells. Little data are available for any wells drilled in the 1970's. Names and detailed location data for geothermal wells are given in Appendix II.

The earlier wells at Beowawe Geysers underwent considerable testing shortly after drilling and for several years thereafter (Middleton, 1961; Oesterling, 1962; Allen, 1962).

Although some of the data are confusing or conflicting, it seems clear that several of the steam wells did produce large flows of steam and hot water from shallow depths. Temperature-depth curves for some of the wells are reproduced in Figure 26. Some of the wells apparently produced at least 400,000 to 500,000 lbs/hr of fluid, with 10 to 15 percent steam flashover. Middleton (1961) reports approximately 1.5 million lbs/hr of fluid at 342°F from the Vulcan No. 4 well, with 41,500 lbs/hr of that being steam. The wellhead pressure was reported to be 116 lbs/in² absolute (psia). Static pressure in several of the wells is apparently in the 40 to 100 psia range, and flow pressure is reportedly 20 to 30 psia. Problems of cold water inflow have been reported because the holes were not cased deeply enough. Scaling in the wells can also be a problem (Koenig, 1970). These problems may have contributed to the general lowering of productivity indicated in test results over a period of several years. No data are available on the productivity of the deeper wells drilled in the mid-1970's.

Unnamed spring, Crescent Valley [97]

The highest hot-spring temperatures in Eureka County are reported from an unnamed spring in NW/4 NW/4 NE/4 S10, T28N, R49E. Wilson (1960a) reports a temperature of 186°F for this spring, which occurs along a major basin-




FIGURE 25. Diagrammatic cross section, looking east-northeast, at Beowawe Geysers, Eureka County (after Oesterling, 1962).




FIGURE 26. Temperatures recorded during drilling of Vulcan Thermal Power Co. wells by cable tool rig at Beowawe Geysers, Eureka County (from Middleton, 1961).

range fault (the Crescent Fault) which has significant displacement.

Hot Springs Point (Crescent Valley) [96]

At least five hot springs are found at Hot Springs Point in Crescent Valley. These are located near the corner of S1, 2, and 11, T29N, R48E and arise from alluvium and bedrock in a line 1.5 miles long. Native sulfur occurs in the Ordovician Valmy Formation along a northwest-trending, nearly vertical fault zone (Keith Papke, personal communication, 1975) just southeast of the hot springs. Hot Springs Point itself is bounded on its northwest and southeast sides by faults. The hot springs fall along the trace of the Dry Hills fault, which extends northeast along the northwest side of Hot Springs Point for about 8 miles. The deposit of native sulfur appears to be associated with the hot-springs activity, and small amounts of cinnabar and antimony occur sporadically throughout the sulfur (Olson, 1964). Spring temperatures fall between 122° and 138°F, except for one spring on the valley floor which is 79°F. A 410-foot-deep geothermal well drilled by Magma Power Co. encountered

subsurface temperatures up to 166°F. The estimated thermal-aquifer temperature for this spring system is 239°F (Mariner and others, 1974). Spring sinter and caliche are reported from along nearby northeast-trending faults which cut Tertiary andesites (Wilson, 1960b). These deposits are in the north half of S6, T29N, R49E. Also, calcareous sinter is reportedly being deposited at the hot springs. Young north- and northeast-trending faults are also common in the alluvial deposits of Crescent Valley in this area.

Walti Hot Springs [102]

Walti Hot Springs in Grass Valley have the third highest reported water temperatures in Eureka County. Several springs are presently depositing siliceous spring sinter (Roberts and others, 1967). Mariner and others (1974) estimate that the reservoir temperature of Walti Hot Springs is probably about 179°F according to a Na-K-Ca geothermometer. The springs lie near a major fault along the west margin of the Simpson Park Mountains (Roberts and others, 1967, plate 3). An alligator is reported to have survived in the hot-spring waters for 16 years in the early

EUREKA COUNTY (continued)

1900's (Nevada Historical Society in the Nevada State Journal, October 17, 1976).

Klobe (Bartholomae) Hot Springs [108]

Water temperatures at Klobe (or Clobe) Hot Springs at the Bartholomae Ranch are reported as high as 156°F in flowing springs (Fiero, 1968) and 158°F in a water well drilled in the spring (Rush and Everett, 1964). At least two springs are present and two or more wells have been drilled at the site of the springs in S28,T18N,R50E. The water is used for stock watering. Mariner and others (1974) report an estimated reservoir temperature of about 163°F from a Na-K-Ca geothermometer. This estimated reservoir temperature is near the reported surface spring temperature. Also, two wells of the Bartholomae Corp. in S18 and 30, T18N,R51E about 4 miles northeast of Klobe Hot Springs have water temperatures of 72° and 74°F. These slightly anomalous temperatures may indicate a large area of thermal ground water in this portion of Antelope Valley.

Bartine Hot Springs [107]

Bartine Hot Springs are located in Antelope Valley about 11 miles north of Klobe Hot Springs, in S5,T19N, R50E, and about 2.5 miles north of the Bartine Ranch along Highway U. S. 50. Waring (1965) reports temperatures of 105° and 108°F for two springs issuing from a "tufa" mound. A flowing well is described from near the Bartine Ranch in S17?, where a 116°F temperature was reported by Fred Bartine. Other artesian wells in the vicinity have temperatures of 58°F. These cold-water wells are probably all in the same water-bearing horizon, but the flow of the hot-water well was not affected by the drilling of the cold wells.



Horseshoe Ranch Springs [93]

Two springs having temperatures of up to 136°F are located in S32,T32N,R49E at Horseshoe Ranch about 1 mile northeast of the town of Beowawe. The flow from these springs is only about 30 gallons per minute; they are reportedly used for bathing and irrigation (Roberts and others, 1967; Stearns and others, 1937). These springs are probably on an extension of a N70°E fault which runs along the south side of Whirlwind Valley. This fault localizes the surface geothermal activity at the Beowawe Geysers 7 miles to the southwest in Eureka County near the Eureka-Lander boundary (see the section on Beowawe Geysers in this county).

Bruffey's (Mineral Hill) Hot Springs [100]

Five or six hot springs and spring systems are located along the margins of the Sulphur Spring Range in southeastern Eureka County, these springs described below are Bruffey's Hot Springs, Shipley Hot Springs, Carlotti Ranch Springs, Siri Ranch Spring, Flynn Ranch Springs, and possibly Sulfur Springs. A prominent fault bounds the Sulphur Springs Range along the west side of Diamond Valley and cuts through the range near Bruffey Canyon; it is apparently coincident with Bruffey's Hot Springs and Carlotti Ranch Springs along the east side of Pine Valley.

Bruffey's Hot Springs (formerly Mineral Hill Hot Springs) has the highest temperatures of those along the trace of the fault. Temperatures are up to 152°F, (Stearns and others, 1937), and calcareous sinter occurs as prominent terraces. Six springs occur along a north-south fault of large displacement. The old travertine deposits here contain barite and fluorite, although the travertine presently being deposited is devoid of barite and fluorite (White, 1955a).

Shipley (Big Shipley, Sadler) Hot Springs [103]

Springs in S23,T24N,R42E known as Shipley, Big Shipley, or Sadler Hot Springs have temperatures up to 106°F and issue from alluvium near the bedrock outcrops. The springs are probably supplied by water moving through secondary openings in Paleozoic rocks (Eakin, 1962a). Reported discharges range from 3,000 to 6,750 gallons per minute.

Carlotti Ranch (Sulfur) Springs [99]

Two springs a quarter of a mile apart have temperatures of 95° and 102°F (Stearns and others, 1937). The springs are used for irrigation. They are along the east side of Pine Valley 5 miles north of Bruffey's Hot Springs and are probably along the same fault reported there.

Siri Ranch Spring [104]

A warm spring and water well are found in S6,T24N, R53E at Siri Ranch along the west side of Diamond Valley north of Shipley's Hot Springs. A small pool in the alluvium is reported (Mifflin, 1968). The reported temperatures vary from 81° to 87°F for the spring, while the well is 95°F. Discharges reported are 5,800 and 300 gallons per minute (Mifflin, 1968; Stearns and others, 1937). These springs are probably associated with the range-front fault along the Sulphur Spring Range here.

EUREKA COUNTY (continued)

Flynn Ranch Springs [101]

The Flynn Ranch Springs consist of several slightly warm springs of low discharge and a deep pool. The temperatures range from 69° to 70°F, and the discharge is reported to be 10 gallons per minute. The springs are located in S5,T25N,R53E, about one-half the distance between Shipley's and Bruffey's Hot Springs, along the west edge of the Sulphur Spring Range.

Sulfur Springs [105]

Two slightly warm springs are located in S36,T23N, R52E along the east side of the Sulphur Spring Range about 8 miles south of Shipley's Hot Springs. The temperature of the springs is 74°F and they discharge about 20 gallons per minute. These springs are near the mountain front, and may be related to a possible extension of the frontal fault near Siri Ranch and just north of Shipley's Hot Springs.

Thompson Ranch Spring [106]

A warm (69° to 75°F) spring issues from alluvium adjacent to limestone at Thompson Ranch on the east side of Diamond Valley in S3,T23N,R54E (Mifflin, 1968). This spring may be the same as the Jacobson Ranch Springs reported by Waring (1965). Harrill (1968) suggests that the spring is probably fault-controlled, as is, according to Roberts and others (1967), a part of the range front along the edge of the Diamond Range.

Hot Creek springs [98]

Six springs flow from alluvium just adjacent to limestone bedrock. The main spring orifice is reportedly in bedrock. The springs are in S12,T28N,R52E (Mifflin, 1968). The reported temperature is 84°F. These springs have reported discharges of 1,800–2,250 (Eakin, 1961) and 5,900 (Mifflin, 1968) gallons per minute. This flow often largely maintains Pine Creek which flows north down the center of Pine Valley. The Na-K-Ca thermal reservoir estimate is near the spring temperature (Mariner and others, 1974).

Raine Ranch? Springs [95]

Springs in S6,T31N,R52E are reportedly warm and flow 100 gallons per minute (Bradberry and Associates, 1964).

HUMBOLDT COUNTY

Double Hot Springs–Black Rock Hot Springs [131]

A number of hot springs are located in alluvium along the west side of the Black Rock Range (fig. 27). These springs are normally 1 mile or less from the bedrock outcrops, and are aligned along a 7 mile long zone from south of Black Rock Point to Double Hot Springs (Hose and Taylor, 1974). The springs are along a major range-boundary fault with slight Holocene displacement which extends north from Black Rock Point to Soldier Meadows, a distance of approximately 35 miles. A hot spring is also present in S10,T37N,R26E about 5 miles north of Double Hot Springs (Waring, 1965), and warm ground was encountered about half a mile north of that spring in a U. S. Geological




FIGURE 27. Geologic map of the Double Hot Springs–Black Rock area (after Hose and Taylor, 1974).

Identification number, name, location	Temp. (°F)	Discharge (gpm)	Date	SiO ₂ (ppm)	Fe (ppm)	Ca (ppm)	Mg (ppm)	Na (ppm)	K (ppm)	HCO ₃ (ppm)	CO ₃ (ppm)	SO ₄ (ppm)	Cl (ppm)	F (ppm)	NO ₃ (ppm)	B (ppm)	TDS (ppm)	SC (µmhos/cm)	pH	Reference	
ESMERALDA COUNTY (continued)																					
well SW¼NW¼S20,T1N,R36E Nevada Oil and Minerals V.R.S. No. 1 well SW¼NE¼NE¼S16,T1S,R36E	77	25	May57	—	—	48	7.4	258	601	0	98	70	70	4.2	—	—	—	1330	7.1	Rush & Katzer, 1973	
Remarks: Depth - 9178 ft; well is an abandoned oil test.	318	—	16Nov70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Nevada Oil & Gas Conservation Commission, unpub. data	
well NE¼S19,T1S,R36E	77	29	Nov49	—	0.17	49	9.6	268	614	—	120	74	74	4.3	—	—	940	—	7	CWRR, 1973	
[86] Southern Big Smoky Valley																					
well NW¼S14,T1N,R37E	71	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Rush & Schroer, 1970	
Remarks: Depth - 546 ft.	80	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Rush & Schroer, 1970	
Emigrant well NW¼S6,T1N,R38E	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Rush & Schroer, 1970	
Fishlake Livestock Co. well SE¼SE¼S5,T1S,R39E	hot	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Rush & Schroer, 1970	
Remarks: Depth - 520 ft; 10 gal/hr seep of hot water was reported at 165 ft; the well is reported to have been destroyed.	hot	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	oral communication, Norman Coombs, 1973	
Remarks: Hot water hit below the 1000-foot level.																					
[87] Pearl Hot Springs																					
springs SE¼NW¼SW¼S25,T1S,R40E	98	—	19Jan67	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	CWRR, 1973	
Remarks: Unsurveyed township																					
[90] Alkali Springs																					
springs NW¼S26,T1S,R41E	140	50	18Jan67	—	—	46	4.6	349	348	—	492	68	68	—	—	—	—	1840	8.1	Rush, 1968a	
springs NW¼S26,T1S,R41E	120-140	59	before 1907	42	—	46	—	282	—	142	—	501	64	—	—	—	—	—	—	Ball, 1907	
Remarks: Fe + Al = 4. Temperature 120° F at tunnel mouth; 140° F at tunnel breast.																					
[91] Silver Peak Hot (Waterworks) Springs																					
springs CSE¼S15,T2S,R39E	69-118	500	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 112	
springs NW¼S26,T1S,R41E	120	40	1913?	42	—	46	—	282	70	—	500	65	65	—	—	—	—	—	—	Meinzer, 1917	
Remarks: Fe + Al = 3.																					
springs SE¼NE¼S26,T1S,R41E	140	45	1905?	42	—	46	—	282	—	142	—	501	64	—	—	—	—	—	—	Ransome, 1909, p. 143	
Remarks: Fe + Al = 3.																					
[92] Silver Peak Hot (Waterworks) Springs																					
springs CSE¼S15,T2S,R39E	77	20	Jan67	—	—	9.6	2.4	238	—	—	—	—	47	—	—	—	—	—	—	Waring, 1965, No. 111	
springs NW¼S6,T1S,R43E																					
EUREKA COUNTY																					
[93] Horseshoe Ranch Springs																					
springs S32,T32N,R49E	136	30	—	58	—	22	5.8	136	17	378	0	62	27	5.0	—	0.81	—	—	—	7.0	Roberts, Montgomery & Lehner, 1967
Remarks: Li = 0, NH ₄ = 6.4.																					
springs S32,T32N,R49E	125-132	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 88	
springs S32,T32N,R49E	—	—	22Feb37	—	—	28	tr	151	—	393	—	60	9	—	—	0.9	—	—	—	Miller, Hardman & Mason, 1953	
1 mi from Beowawe																					
[94] Beowawe Geysers																					
springs SE¼S8,T31N,R48E	208	26	1973	320	—	1.0	<0.1	230	16	321	32	130	69	17	—	2.1	—	1020	9.0	Mariner & others, 1974	
Remarks: Li = 1.3.																					
well SW¼SW¼SW¼S9,T31N,R48E	77	—	—	125	—	16	1.4	220	17	440	—	100	49	11	—	1.7	757	1090	7.6	Olmsted & Rush, 1977	
Remarks: Li = 1700µg/l.																					
springs S17,T31N,R48E	190	—	—	330	—	1.0	—	210	8	—	—	—	56	—	—	—	—	—	—	Wollenberg & others, 1977	
Remarks: U < 0.2µg/l, Ba = 50µg/l, W = 150µg/l, Br = 135µg/l, Sb = 13µg/l, Mo = 19µg/l, Rb = 145µg/l, Cs = 200µg/l, As = 40µg/l, Fe < 70µg/l, Sc < 0.02µg/l, Mn < 3µg/l.																					

Identification number, name, location	Temp. (°F)	Discharge (gpm)	Date	SiO ₂ (ppm)	Fe (ppm)	Ca (ppm)	Mg (ppm)	Na (ppm)	K (ppm)	HCO ₃ (ppm)	CO ₃ (ppm)	SO ₄ (ppm)	Cl (ppm)	F (ppm)	NO ₃ (ppm)	B (ppm)	TDS (ppm)	SC (µmhos/cm)	pH	Reference	
EUREKA COUNTY (continued)																					
acidic spring S17,T31N,R48E	172	Remarks: U = 0.5µg/l, Ba = 190µg/l, W = 12µg/l, Br = 120µg/l, Sb = 5µg/l, Mo = 3µg/l, As = 115µg/l, Cs = 115µg/l, Fe = 670µg/l, Sc = 0.7µg/l, Mn = 115µg/l.	300	3	250	31	42	42	42	42	42	42	42	42	42	42	42	42	42	42	Wollenberg & others, 1977
hot spring S17,T31N,R48E	183	Remarks: PO ₄ <0.1, NH ₄ = 0.5, Ag <0.02, As = 2.2µg/l, Ba <0.04, Be <0.005, Bi <0.1, Cd <0.01, Cr <0.002, Cs = 1.04, Cu <0.01, Hg <0.5µg/l, Li = 2.59, Mn = 0.14, Ni = 0.05, Pb = 0.06, Rb = 0.266, Sb <0.1, Se <1.0µg/l, Sn = 0.05, Sr = 0.015, Zn = 2.32.	345	.09	0.82	229	14.2	0	152	128	67	18.7	<0.1	964	1006	9.7	Sanders & Miles, 1974				
spring S17,T31N,R48E	205	Remarks: Al = 444, Ni = 0.05, Pb = 0.06, Rb = 0.266, Sb <0.1, Se <1.0µg/l, Sn = 0.05, Sr = 0.015, Zn = 2.32.	444	<1	241	29	148	161	78	44	44	2.2	1100	9.5	White, 1964						
spring S17,T31N,R48E	190	Remarks: U = <0.26 ppb; W = 147 ppb; Mo = 19 ppb; Sb = 13 ppb; Ba 61 ppb.	207	207	207	207	207	207	207	207	207	207	207	207	207	207	207	207	207	207	Wollenberg & others, 1975
boiling S17,T31N,R48E	boiling	Remarks: Stream sample. U <0.16 ppb; W = 132 ppb; Mo = 12 ppb; Sb = 10 ppb; Ba = 50 ppb. Duplicate analysis agrees closely.	268	268	268	268	268	268	268	268	268	268	268	268	268	268	268	268	268	268	Wollenberg & others, 1975
hot spring S17,T31N,R48E	170	Remarks: Al + Fe = tr.	413	tr	0	216	244	84	84	30	30	30	30	30	30	30	30	30	30	30	Nolan & Anderson, 1934
small geyser S17,T31N,R48E	170	Remarks: Al = 0, As = 0, NH ₄ = 4, S ₂ O ₃ = 1, H ₂ S = 0. Several species of diatoms live in the warm pools.	449	tr	2	0	239	33	129	173	97	11	7	7	7	7	7	7	7	7	Nolan & Anderson, 1934
pool below terrace S17,T31N,R48E	205	Remarks: Al = 0, Mn = 0, Li = 1.3, NH ₄ = 0.5, Br = 0.4, H ₂ S = 5.5, Sr = 0, I = 0.	373	0.04	0.8	0	230	16	116	149	89	30	15	0.4	2.0	9.5	Roberts, Montgomery & Lehner, 1967				
geyser S17,T31N,R48E	170	Remarks: Al + Fe = tr.	418	tr	tr	282	512	tr	91	70	70	70	70	70	70	70	70	70	70	70	Nolan & Anderson, 1934; Waring, 1965, No. 77A
Beowawe Hot Springs	170	Remarks: Fe + Al = tr.	413	tr	0	216	244	84	84	30	30	30	30	30	30	30	30	30	30	30	Adams, 1944
hot springs	170	Remarks: Fe + Al = tr.	418	tr	0	282	512	tr	91	70	70	70	70	70	70	70	70	70	70	70	Adams, 1944
Flame Geyser	170	Remarks: Fe + Al = tr.	418	tr	0	282	512	tr	91	70	70	70	70	70	70	70	70	70	70	70	Miller, Hardman & Mason, 1953
steam well NW¼S17,T31N,R48E	170	Remarks: U = 1973, 500	500	1.3	0.2	250	38	505	81	64	70	<0.05	2.5	1490	9.4	Mariner & others, 1974					
well S17,T31N,R48E	steam	Remarks: Li = 2.1.	490	1.5	280	40	67	67	67	67	67	67	67	67	67	67	67	67	67	67	Wollenberg & others, 1977
Sierra Pacific Power Co. well S17,T31N,R48E	385	Remarks: From most northerly blowing well; U <0.07µg/l, Ba = 50µg/l, W = 135µg/l, Br = 145µg/l, Sb = 11µg/l, Mo = 11µg/l, Cs = 320µg/l, Sc = 220µg/l, As = 33µg/l, Fe <90µg/l, Se <0.02µg/l, Mn <3µg/l.	458	0.05	10	0	263	31	0	288	127	16	<0.1	1256	1211	9.9	Roberts, Montgomery & Lehner, 1967				
steam well S17,T31N,R48E	boiling	Remarks: PO ₄ <0.1, NH ₄ = 0.9, Ag <0.004, As = 21µg/l, Ba <0.10, Be <0.005, Bi <0.10, Cd <0.002, Cr <0.04, Cs = 1.02, Cu <0.004, Hg <0.2µg/l, Li = 3.2, Mn <0.01, Nb <10, Ni = 0.03, Pb <0.02, Rb = 0.63, Sb <0.2, Se <1µg/l, Sn <0.2, Sr = 0.04, Ta <5, Zn = 0.01.	458	0.05	10	0	263	31	0	288	127	16	<0.1	1256	1211	9.9	Sanders & Miles, 1974				
Nevada Thermal (Magma Power Co.) No. 2 well NW¼S17,T31N,R48E	boiling	Remarks: Al = 0.66, Fe = 0.00, As = 0.00, Sr = 0.21, Li = 1.6, NH ₄ = 0.4, I = 0.0, PO ₄ = 0.06, Br = 0.0. Sample may be 10 percent evaporated by boiling.	534	0.8	0.2	332	30	39	224	90	49	15	0.0	2.4	1200	9.7	White, 1964				
Vulcan Thermal Power Co. No. 1 well NW¼SE¼SW¼NW¼ S17,T31N,R48E	414	Remarks: Depth - 638 ft.	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	1961	unpublished data, Sierra Pacific Power Co.
[95] Raine Ranch(?) springs S6,7,T31N,R52E	warm	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	100+	Bradberry & Associates, 1964
[96] Hot Springs Point (Crescent Valley) Crescent Valley Hot Springs SW¼S1,T29N,R48E	138	100	10Jun48	73	0.03	53	43	319	980	117	44	5.9	0.0	0.4	1140	1750	Zones, 1961b				
spring SW¼S1,T29N,R48E	124	0	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	Wilson, 1960b
spring NE¼S1,T29N,R48E	124	15	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	Wilson, 1960b
spring SW¼S2,T29N,R48E	136	8	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	Wilson, 1960b
spring SE¼SE¼S2 & NE¼NE¼ S11,T29N,R48E	138	40	72	0.04	54	38	277	51	928	0	116	49	6.9	3.3	1.6	6.8	Roberts, Montgomery & Lehner, 1967				

Identification number, name, location	Temp. (°F)	Discharge (gpm)	Date	SiO ₂ (ppm)	Fe (ppm)	Ca (ppm)	Mg (ppm)	Na (ppm)	K (ppm)	HCO ₃ (ppm)	CO ₃ (ppm)	SO ₄ (ppm)	Cl (ppm)	F (ppm)	NO ₃ (ppm)	B (ppm)	TDS (ppm)	SC (µmhos/cm)	pH	Reference	
EUREKA COUNTY (continued)																					
spring NW¼S11,T29N,R48E	129	33	1973	67	—	53	35	230	58	913	<1	7	1	6.6	—	2.1	—	1730	6.6	Mariner & others, 1974	
		Remarks: Li = 1.1.																			
spring NE¼S11,T29N,R48E	—	Remarks: Al = 0.008, N = 3.2, P = 0.01, Br = 0.2, I = 0.02, Rb = 0.29, Ce = 0.1, Sr = 1.3, Cu = 0.04, Hg = <0.0001, δD(‰) = -125.8, δO ¹⁸ = -13.21; gas (volume %): O ₂ + Ar = 9, N ₂ = 31, CH ₄ <1, CO ₂ = 60.																			
spring SE¼SE¼S2 & NE¼NE¼S11,T29N,R48E	122	15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 88A	
Magma Power Co. Hot Springs Point No. 1 well S1,2 or 11, T29N,R48E	166	—	1965	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Koenig, 1970	
		Remarks: Depth - 410 ft.																			
[97] spring NW¼NW¼NE¼S10,T28N,R49E	186	2.5	1960	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Wilson, 1960a	
[98] Hot Creek Springs																					
spring NW¼S12,T28N,R52E	79	1585	1973	20	—	46	23.5	10	2.1	226	1	27	4.6	<0.1	—	0.03	—	408	7.3	Mariner & others, 1974	
		Remarks: Li = 0.02.																			
spring SW¼NW¼S12,T28N,R52E	84	5900	27Sep65	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Mifflin, 1968; Waring, 1965, No. 89	
		Remarks: (epm) Na + K = 0.53; Ca + Mg = 3.77; Cl + SO ₄ = 0.74.																			
spring SE¼NW¼S12,T28N,R52E	—	1800-2250	1960	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Eakin, 1961b	
[99] Carlotti Ranch (Sulfur) Springs																					
spring SE¼S24,T28N,R52E	95-102	100	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 90	
[100] Bruffey's (Mineral Hill) Hot Springs																					
spring S14,T27N,R52E	150	50	—	.58	—	52	16	39	8.7	2.87	0	27	14	0.7	0.1	0.25	—	—	—	7.0 Roberts, Montgomery & Lehner, 1967	
		Remarks: Mn = 0; Ba = 0; Li = 0.2.																			
spring S14,T27N,R52E	108-152	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 90A	
[101] Flynn Ranch Springs																					
spring S5,T25N,R53E	69-78	10	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 91	
[102] Walti Hot Springs																					
spring W¼S33,T24N,R48E	163	—	—	75	0.02	60	13	48	15	282	0	62	13	2.4	0.1	0.17	—	—	—	6.9 Roberts, Montgomery & Lehner, 1967	
		Remarks: Mn = 0; Li = 0; PO ₄ = 0.1.																			
spring S33,T24N,R48E	160	—	17Jun65	—	—	57	12	70	—	315	0	65	14	—	—	—	—	—	—	7.1 Everett & Rush, 1966	
spring SW¼S33,T24N,R48E	162	79	1973	68	—	56	12	44	14	264	<1	64	12	2.5	—	0.12	—	592	6.5	Mariner & others, 1974	
		Remarks: Li = 0.3.																			
spring W¼S33,T24N,R48E	160	897	17Jun65	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Mifflin, 1968	
		Remarks: (epm) Na + K = 3.04; Ca + Mg = 3.82; Cl + SO ₄ = 1.75.																			
spring S33,T24N,R48E	hot	small	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 93	
[103] Shipley (Big Shipley, Sadler) Hot Springs																					
spring NE¼SE¼S23,T24N,R52E	103-106	5000	1960	40	0.01	57	21	29	5.9	279	0	35	21	0.2	0	0.26	346	540	7.2	Eakin, 1962a; Waring, 1965, No. 91B	
		Remarks: Mn = 0; Li = 0; PO ₄ = 0.1.																			
spring NE¼SE¼S23,T24N,R52E	94	3000	16Apr63	30	0	55	21	30	5	288	0	33	17	0.5	0.6	0.1	330	529	7.6	Harrill, 1968	
spring NE¼SE¼S23,T24N,R52E	106	6750	18Sep52	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Mifflin, 1968	
		Remarks: (epm) Na + K = 1.52; Ca + Mg = 4.57; Cl + SO ₄ = 1.29.																			
[104] Sirt Ranch Spring																					
spring NW¼SW¼S6,T24N,R53E	81	5800	11Jul66	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Mifflin, 1968	
		Remarks: (epm) Na + K = 0.76; Ca + Mg = 4.00; Cl + SO ₄ = 0.89.																			
spring NW¼SW¼S6,T24N,R53E	87	300	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Waring, 1965, No. 91A	

Identification number, name, location	Temp. (F)	Discharge (gpm)	Date	SiO ₂ (ppm)	Fe (ppm)	Ca (ppm)	Mg (ppm)	Na (ppm)	K (ppm)	HCO ₃ (ppm)	CO ₃ (ppm)	SO ₄ (ppm)	Cl (ppm)	F (ppm)	NO ₃ (ppm)	B (ppm)	TDS (ppm)	SC (µmhos/cm)	pH	Reference	
EUREKA COUNTY (continued)																					
water well SW¼NE¼S6,T24N,R53E	95	-	5May66	25	0	51	20	15	3.4	255	0	25	10	0.4	0.5	0	276	449	8.0	Harrill, 1968	
[105] Sulfur Springs																					
springs NW¼S36,T23N,R52E	74	20	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Waring, 1965, No. 91C	
[106] Thompson Ranch Spring																					
springs NW¼SE¼S3,T23N,R54E	69	950	1Apr66	19	0.01	73	22	23	5.1	318	0	51	6.5	0.4	1.1	0	358	583	7.8	Harrill, 1968	
Jacobson Ranch Springs NW¼SE¼S3,T23N,R54E	71-75	900	11Jul66	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Mifflin, 1968; Waring, 1965, No. 91D	
Remarks: (gpm) Na + K = 1.14; Ca + Mg = 5.03; Cl + SO ₄ = 1.47.																					
[107] Bartine Hot Springs																					
springs NE¼NE¼S5,T19N,R50E	105, 108	10	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Waring, 1965, No. 93A	
Bartine Ranch water well no. 4 NE¼S17,T19N,R50E	116	33	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	information from Fred Bartine	
Remarks: Depth - 485 ft; artesian.																					
[108] Klobe (Bartholomae) Hot Springs																					
springs NW¼SE¼S28,T18N,R50E	130	450	15Apr64	87	0.02	2.2	1.7	6.5	0.7	126	10	18	6.5	4.0	0	0.08	-	-	-	8.5 Roberts, Montgomery & Lehner, 1967	
Remarks: Mn = 0; Li = 0; PO ₄ = 0.																					
springs NW¼NW¼SE¼S28,T18N,R50E	153	49(1966)	18Sep73	82	0.04	10.3	.002	66	1.0	66.4	40.5	16.2	11	4.8	<0.1	-	265	304	-	9.4 Sanders & Miles, 1974	
Remarks: Li = 0.11, As = 0.024, Ba = 0.1, NH ₄ < 0.1, PO ₄ < 0.1, Be < 0.005, Cu < 0.004, Pb < 0.02, Mn < 0.01, Sr < 0.02, Cd < 0.002, Cr < 0.04, Ag < 0.04, Bi < 0.10, Cs = 24, Hg < 0.24µg/l, Nb < 10.0, Rb < 0.02, Sb < 0.2, Se < 0.01, Sn < 0.2, Ta < 5.0, Zn < 0.01. In Antelope Valley, 8 mi S of U. S. Hwy. 50. Spring flows from vertical 12" steel pipe approximately 50 ft SW of corral. Orifice is in alluvium 2 mi E of Monitor Range. Spring may be associated with buried range front fault.																					
springs SE¼S28,T18N,R50E	129	-	1973	85	-	1	<0.1	64	0.7	144	-	18	6.3	-	-	-	295	-	-	9.3 Mariner & others, 1974	
springs NW¼NW¼SE¼S28,T18N,R50E	156	49	21Dec66	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Fiero, 1968	
springs NW¼SE¼S28,T18N,R50E	142	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Waring, 1965, No. 93B	
Hot Spring Ranch water well NW¼NW¼SE¼S28,T18N,R50E	158	-	21May64	-	-	0	0	71	-	94	26	22	7.1	-	-	-	-	315	-	9.0 Rush & Everett, 1964	
Remarks: Well drilled in Klobe (Clobe) Hot Spring.																					
Hot Spring Ranch water well NW¼NW¼SE¼S28,T18N,R50E	158	3	21Dec66	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Fiero, 1968	
Remarks: Flowing well; depth - 39.5 ft.																					
Hot Spring Ranch water well NW¼NW¼SE¼S28,T18N,R50E	72	-	21May64	-	-	0	0	72	-	92	29	22	7.3	-	-	-	-	319	-	9.1 Rush & Everett, 1964	
Remarks: Depth - 35 ft.																					
"cold" spring NW¼NW¼SE¼S28,T18N,R50E	70	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Fiero, 1968	
Bartholomae Corp. water well SW¼S18,T18N,R51E	74	14	1949	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Rush & Everett, 1964	
Remarks: Depth - 670 ft; flowing.																					
Bartholomae Corp. water well NW¼S30,T18N,R51E	72	200	16Apr64	-	-	24	7.8	36	-	135	12	28	7.0	-	-	-	-	319	-	8.7 Rush & Everett, 1964	
HUMBOLDT COUNTY																					
[109] Cordero Mercury Mine																					
Cordero Mining Co. well SE¼S28,T47N,R37E	140	-	-	57	tr	36	10	62	195	-	-	56	34	-	-	-	365	500	-	Visher, 1957	
Remarks: Depth - 442 ft.																					
Cordero Mining Co. well SE¼S28,T47N,R37E	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Holmes, 1966	
Remarks: Hot water is pumped from a 600 ft deep well at 10 gpm for domestic uses; it is augmented by 8 gpm of cold water.																					
Cordero Mining Co. well S28,T47N,R37E	138	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	White, 1955a; Waring, 1965, No. 6A	
Remarks: Depth - 580 ft.																					
Cordero Mining Co. well S28,T47N,R37E	118	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	White, 1955; Waring, 1965, No. 6A	
Remarks: Depth - 550 ft.																					
Noque's Nevada well NE¼NE¼SE¼S17,T47N,R38E	92	-	16Jun77	110	0.00	5.8	0.2	58	12	119	-	26	14	2.6	2.4	0.37	322	323	-	unpublished data, USGS	
Remarks: Depth - 701 ft.																					