



SOUTHERN NEVADA
WATER AUTHORITY

Water Resources Division

2013 Delamar, Dry Lake, and Cave Valleys Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report

March 2014

Prepared by
Southern Nevada Water Authority
Water Resources Division
P.O. Box 99956
Las Vegas, Nevada 89193-9956

Submitted to the
Nevada State Engineer
and the DDC Stipulation
Executive Committee

This document's use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the Southern Nevada Water Authority. Although trademarked names are used, a trademark symbol does not appear after every occurrence of a trademarked name. Every attempt has been made to use proprietary trademarks in the capitalization style used by the manufacturer.

Suggested citation:

Southern Nevada Water Authority, 2014, 2013 Delamar, Dry Lake, and Cave Valleys hydrologic monitoring, management, and mitigation plan status and data report: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0024, 109 p.

CONTENTS

List of Figures	iii
List of Tables	v
List of Acronyms and Abbreviations	vii
1.0 Introduction.....	1-1
1.1 Background.....	1-1
1.2 Major Activities Performed in 2013.....	1-3
1.3 Report Scope.....	1-3
2.0 DDCMM Plan Status and Data.....	2-1
2.1 Hydrologic Monitoring Program	2-1
2.2 Monitor-Well Network.....	2-1
2.2.1 Existing-Well Monitoring Network.....	2-1
2.2.2 Future Monitor Wells.....	2-4
2.2.3 Exploratory- and Production-Well Monitoring	2-5
2.2.4 Aquifer Testing.....	2-8
2.3 Spring Monitoring Network	2-8
2.3.1 White River and Pahrnagat Valleys Springs	2-8
2.3.1.1 Flag Springs	2-9
2.3.1.2 Hardy Springs	2-11
2.3.1.3 Moorman Spring	2-11
2.3.1.4 Hot Creek Spring	2-11
2.3.1.5 Ash Springs	2-13
2.3.1.6 Crystal Springs	2-13
2.3.1.7 Hiko Spring	2-13
2.3.1.8 Maynard Spring	2-14
2.3.1.9 Cottonwood Spring	2-14
2.3.2 DDC Springs Biannual Monitoring	2-14
2.3.2.1 Cave Spring	2-15
2.3.2.2 Parker Station	2-15
2.3.2.3 Lewis Well	2-16
2.3.2.4 Silver King Well	2-16
2.3.2.5 Coyote Spring	2-16
2.3.2.6 Big Mud Springs	2-16
2.3.2.7 Littlefield Spring	2-17
2.3.2.8 Grassy Spring	2-17
2.4 Precipitation-Station Network	2-17
2.5 Water Chemistry.....	2-20
2.6 Data Reporting	2-20
2.7 Proposed Schedule of Groundwater Withdrawals	2-21
3.0 Anticipated 2014 SNWA DDCMM Plan Activities.....	3-1
4.0 References.....	4-1



CONTENTS (CONTINUED)

Appendix A - Periodic Water-Level Measurement Data from the DDC Existing-Well Monitoring Network

Appendix B - Continuous Water-Level Measurement Data from the DDC Existing-Well Monitoring Network

Appendix C - Periodic Water-Level Measurements and Hydrographs for SNWA Exploratory and Test Wells

Appendix D - Spring Discharge Measurements and Hydrographs

Appendix E - 2013 DDC Springs Site Photos

Appendix F - Regional and High-Altitude Precipitation-Station Data

FIGURES

NUMBER	TITLE	PAGE
1-1	Primary Study Area Location	1-2
2-1	DDC Monitor-Well and Spring Network	2-2
2-2	SNWA DDC Exploratory Wells	2-7
2-3	Locations of Springs Associated with the DDCMM Plan	2-10
2-4	Hardy Springs Original Condition	2-12
2-5	Hardy Springs Modified Condition	2-12
2-6	DDC Precipitation-Station Locations	2-19
E-1	Maynard Spring, May 2013	E-2
E-2	Maynard Spring, October 2013	E-2
E-3	Cave Spring, May 2013	E-3
E-4	Cave Spring, October 2013	E-3
E-5	Parker Station, May 2013	E-4
E-6	Parker Station, October 2013	E-4
E-7	Parker Station Flume, October 2013	E-5
E-8	Lewis Well, May 2013	E-6
E-9	Lewis Well, October 2013	E-6
E-10	Lewis Well Spring Collector Line Access Discharge, October 2013	E-7
E-11	Silver King Well, May 2013	E-8
E-12	Silver King Well, October 2013	E-8
E-13	Coyote Spring, May 2013	E-9
E-14	Coyote Spring, October 2013	E-9
E-15	Big Mud Spring, May 2013	E-10



FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
E-16	Big Mud Spring, October 2013	E-10
E-17	Littlefield Spring, May 2013	E-11
E-18	Littlefield Spring, October 2013.....	E-11
E-19	Grassy Spring, May 2013.....	E-12
E-20	Grassy Spring, October 2013	E-12

TABLES

NUMBER	TITLE	PAGE
2-1	DDC Existing-Well Monitoring Network	2-3
2-2	Future DDC Monitor Wells	2-4
2-3	SNWA DDC Exploratory Wells.....	2-6
2-4	DDC Springs Monitoring Locations and Monitoring Frequency.....	2-9
2-5	DDC Precipitation-Station Locations	2-18
2-6	Water-Chemistry Parameters	2-21
A-1	Periodic Water-Level Measurement Data from the DDC Existing-Well Monitoring Network.....	A-1
B-1	Cave Valley Well 180W902M, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-2
B-2	Cave Valley Well 180W501M, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-4
B-3	Delamar Valley Well 182M-1, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-6
B-4	Dry Lake Valley Well 181M-1, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-8
B-5	Dry Lake Valley Well 380531114534201, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-10
B-6	Pahrnagat Valley Well 209M-1, Calendar Year 2013 Water-Level Data, Daily Mean Values	B-12
C-1	Periodic Water-Level Measurements Collected at SNWA Exploratory and Test Wells	C-1
D-1	Spring Discharge Measurements	D-1
D-2	Discharge Measurement Summary of Flag Springs Complex	D-6
D-3	Discharge Measurement Summary of Hardy Springs	D-7
D-4	Annual Discharge at Crystal Springs	D-7



TABLES (CONTINUED)

NUMBER	TITLE	PAGE
D-5	Annual Discharge at Ash Springs.....	D-9
D-6	Station Number 2090102 - Hiko Spring at Hiko, NV, Water Year 2013 Mean Daily Discharge Values	D-11
D-7	Station Number 2071302 - Flag Spring 2 near Sunnyside, NV, Water Year 2013 Mean Daily Discharge Values	D-13
F-1	2013 Regional Precipitation Data.....	F-1
F-2	2013 High-Altitude Precipitation Data.....	F-4

ACRONYMS

BLM	Bureau of Land Management
BRT	Biological Resource Team
DDC	Delamar, Dry Lake, and Cave valleys
DOI	U.S. Department of the Interior
EC	Executive Committee
EPA	U.S. Environmental Protection Agency
JFA	Joint Funding Agreement
NAD83	North American Datum of 1983
NAVD88	North American Vertical Datum of 1988
NDOW	Nevada Department of Wildlife
NDWR	Nevada Division of Water Resources
NOAA	National Oceanic and Atmospheric Administration
NRCS	Natural Resources Conservation Service
NSE	Nevada State Engineer
NWS	National Weather Service
SNOTEL	SNOWpack TELEmetry
SNWA	Southern Nevada Water Authority
SR	State Route
TRP	Technical Review Panel
US 93	U.S. Highway 93
USDA	U.S. Department of Agriculture
USFWS	U.S. Fish and Wildlife Service
USGS	U.S. Geological Survey
UTM	Universal Transverse Mercator
WRCC	Western Regional Climate Center

ABBREVIATIONS

°C	degrees Celsius
afy	acre-feet per year
amsl	above mean sea level
bgs	below ground surface
cfs	cubic feet per second
cm	centimeter
ft	foot



ABBREVIATIONS (CONTINUED)

gal	gallon
gpm	gallons per minute
in.	inch
L	liter
m	meter
mg	milligram
mi	mile
µg	microgram
µm	micrometer
µmho	micromho
µS	microsiemen
pmc	percent modern carbon

1.0 INTRODUCTION

This report was prepared by the Southern Nevada Water Authority (SNWA) in satisfaction of monitoring and reporting requirements set forth in the *Hydrologic Monitoring and Mitigation Plan for Delamar, Dry Lake, and Cave Valleys* (DDCMM Plan) (SNWA, 2011a). The location of the primary study area associated with this report is presented in [Figure 1-1](#). This is the seventh hydrologic data report in a series of reports associated with the Delamar, Dry Lake, and Cave valleys (DDC) hydrologic monitoring, management, and mitigation program. The reports document historic hydrologic conditions and plan status since 2007 (SNWA, 2008, 2009b, 2010, 2011b, 2012, and 2013).

The report provides the Nevada State Engineer (NSE) hydrologic data collected in 2013 and the current status of each element of the DDCMM Plan. This report also satisfies the hydrologic data reporting requirements of the U.S. Department of the Interior (DOI) and SNWA Stipulation Agreement. The DDCMM Plan contains all the hydrologic monitoring elements of the Stipulation Agreement, as well as, monitoring related to existing non-federal water-rights as required by the NSE.

1.1 Background

On January 7, 2008 prior to the NSE hearing for applications 53987 to 53992, a Stipulation for Withdrawal of Protests (Stipulation, 2008) was established between SNWA and DOI on behalf of the Bureau of Indian Affairs, the Bureau of Land Management (BLM), the National Park Service, and the U.S. Fish and Wildlife Service (USFWS) (collectively known as the DOI Bureaus). Exhibits A and B of the Stipulation require the development of biologic and hydrologic monitoring plans. As part of the Stipulation, an Executive Committee (EC) was established to oversee the implementation of the agreement. A Technical Review Panel (TRP), composed of technical expert representatives of parties to the stipulation, was established to develop and oversee implementation of the hydrologic monitoring, management, and mitigation plan. A Biological Resource Team (BRT) was also established to oversee the development and implementation of the biological monitoring plan.

On July 9, 2008, SNWA was granted groundwater rights in DDC hydrographic areas (HA180-182) for municipal and domestic purposes under permits 53987 through 53992. Ruling 5875 required the development of biologic and hydrologic monitoring plans. The hydrologic DDCMM Plan associated with this ruling was approved by the NSE on December 22, 2009.

Since the issuance of Ruling 5875, an opinion by the Nevada Supreme Court required that the NSE re-notice SNWA's original groundwater applications and reopen the protest period (Great Basin Water Network, et. al. v. NSE, et. al., June 17, 2010) (NSC, 2010). A new hearing was held by the NSE in regard to the water-right applications in September through November, 2011. On March 22, 2012, the




Figure 1-1
Primary Study Area Location

NSE issued Rulings 6165 through 6167 granting SNWA DDC Application Numbers 53987 through 53992. Rulings 6165 through 6167 approved the SNWA Hydrologic Monitoring and Mitigation Plan for DDC and required annual data reports be submitted to the NSE.

1.2 Major Activities Performed in 2013

Major activities associated with the DDCMM Plan performed in 2013 are as follows:

- Continued implementation of the DDCMM Plan.
- Performed periodic water-level measurements on monitoring network wells. Maintained continuous water-level and spring discharge recording instrumentation at locations specified in the plan.
- Submitted required monitoring data quarterly to the NSE and the TRP. Maintained the SNWA data-exchange web site accessible by NSE, EC, TRP, and BRT.
- Maintained BLM right-of-way access for three future monitor-well locations.

1.3 Report Scope

[Section 2.0](#) of this report presents the hydrologic data collected from the groundwater, spring, and precipitation monitoring networks associated with the DDCMM Plan. [Section 3.0](#) presents anticipated activities in 2014. [Section 4.0](#) documents report references. [Appendix A](#) through [Appendix F](#) present tables and graphs of various hydrologic data discussed in the report. Photos documenting 2013 spring and fall conditions of program springs located within DDC are also presented.



This Page Left Intentionally Blank

2.0 DDCMM PLAN STATUS AND DATA

The hydrologic data collected in 2013 and the current status of each major element of the DDCMM Plan are presented in this section. Each subsection follows the order of topic presentation in the plan.

2.1 Hydrologic Monitoring Program

The DDCMM Plan established a hydrologic monitoring program and network to collect data for the purposes of defining baseline hydrologic conditions prior to SNWA groundwater withdrawals in DDC and evaluating the effects of these withdrawals. The network includes monitor wells and springs located within DDC and adjacent hydrographic areas. The monitoring locations are presented on [Figure 2-1](#). The program also includes reporting of available regional precipitation-station data with an established historical record.

2.2 Monitor-Well Network


The DDCMM Plan includes monitoring of new and existing wells completed in the basin-fill, carbonate-rock, and volcanic-rock aquifers at strategic locations to provide representative groundwater data spatially across the program area. Monitor-well locations were selected with consideration of the hydrogeologic conditions at each location. Geologic reconnaissance, stratigraphic and structural field mapping, aerial photo documentation, surface geophysics, and a review of existing hydrogeologic data were performed to assist in well-site selection. This network will provide long-term monitoring and early detection of drawdown propagation, if any, induced by SNWA groundwater development that might adversely affect existing water-right holders and groundwater-dependent areas sustaining critical habitat for endangered and/or threatened species.

2.2.1 Existing-Well Monitoring Network

SNWA collects continuous groundwater level data at six representative monitor wells in the project area. Groundwater levels are also measured quarterly at nine additional network well locations associated with the DDCMM Plan. This network includes seven SNWA wells, three private wells, four U.S. Geological Survey (USGS-MX) wells, and one BLM well located in DDC and the adjacent White River Valley and Pahranaagat Valley hydrographic areas. The locations of the monitor wells in the network are shown on [Figure 2-1](#). Well-location coordinates, elevation, construction attributes, and monitoring frequencies are presented in [Table 2-1](#). A professional survey of location coordinates, ground-surface elevations, and measuring-point elevations of the wells has been completed.

SNWA constructed seven monitor wells associated with this network in 2005. These consist of four 6-in. diameter and three 12-in. diameter monitor wells in DDC. Geologic analysis reports were

This Page Intentionally Left Blank



Note: Flag Springs Complex has been monitored biannually; continuous monitoring of Flag Spring 2 was implemented in fall 2009.

Figure 2-1
DDC Monitor-Well and Spring Network

**Table 2-1
DDC Existing-Well Monitoring Network**

SNWA Site Number	NDWR Station Local Number ^b	Location ^a		Surface ^c Elevation (ft amsl)	Completion Date	Drill Depth (ft bgs)	Well Depth (ft bgs)	Well Casing Diameter (in.)	Screened Interval (ft bgs)	Open Interval (ft bgs)	Aquifer	Monitor Frequency
		UTM Northing (m)	UTM Easting (m)									
180W902M	180 N06 E64 19ADCC1	4,248,355.59	689,816.08	5,984.89	10/19/2005	917	903	12	195-882	77-917	Carbonate	Continuous
382807114521001	180 N07 E63 14BADD1	4,259,963.15	685,737.56	6,012.39	9/30/1980	460	460	10	210-250, 375-435	40-460	Carbonate ^d	Quarterly
383307114471001	180 N08 E64 15CBCB1	4,269,378.23	692,859.57	6,162.55	---	---	---	7	---	---	Basin Fill	Quarterly
180W501M	180 N09 E64 31CBBD1	4,273,712.79	687,971.03	6,428.63	9/23/2005	1,215	1,212	6	788-1,192	54-1,215	Carbonate	Continuous
182W906M	182 S07 E64 19ACDB1	4,133,304.57	690,065.21	4,796.96	9/2/2005	1,735	1,703	6	1,275-1,678	130-1,735	Volcanic	Quarterly
182M-1	182 S07 E63 18AAAA1	4,135,293.37	680,867.32	4,597.78	7/10/2005	1,345	1,331	12	1,006-1,290	58-1,345	Volcanic	Continuous
372639114520901	182 S06 E63 12AD 1	4,146,220.24	688,472.41	4,706.30	5/10/1980	1,215	1,195	10	920-980, 1,040-1,180	40-1,215	Basin Fill	Quarterly ^e
181W909M	181 S03 E65 07CCDA1	4,174,462.59	698,676.17	4,799.41	10/16/2007	1,285	1,260	12	637-1,240	183-1,285	Basin Fill	Quarterly
181M-1	181 N01 E63 36ABAA1	4,198,199.90	688,534.99	4,963.07	8/30/2005	1,501	1,471	6	765-1,451	58-1,501	Carbonate	Continuous
380531114534201	181 N03 E63 27CAA 1	4,218,085.09	683,720.32	5,456.35	1/1/1981	2,395	2,395	10	---	775-2,395	Carbonate	Continuous ^d
209 S07 E62 20AA 1	209 S07 E62 20AA 1	4,133,610.32	672,648.88	4,082.46	1/10/1981	695	695	8	600-695	55-695	Basin Fill/ Volcanic	Quarterly
373405115090001	209 S04 E61 28CD 1	4,159,504.38	663,314.66	4,230.58	9/19/1968	1,314	1,314	12	1,200-1,300	52-1,314	Basin Fill/ Volcanic	Quarterly
373803115050501	209 S04 E61 01AACB1	4,166,944.29	668,927.03	4,528.90	---	---	700	8	---	---	Basin Fill	Quarterly
209M-1	209 S03 E62 35DAAD1	4,168,065.79	677,323.46	5,097.30	8/4/2005	1,616	1,616	6	1,274-1,595	50-1,616	Carbonate	Continuous
383133115030201	207 N08 E62 30CD 1	4,265,229.62	689,732.25	5,290.20	---	---	101	2	---	---	Basin Fill	Quarterly

^aProfessional survey complete on location and elevation. All coordinates are Universal Transverse Mercator, North American Datum, 1983, Zone 11.

^bStation Local Numbers provided by the Nevada Division of Water Resources.

^cElevations are North American Vertical Datum of 1988 (NAVD88).

^dCarbonate bedrock was encountered at 265 ft bgs according to the well log.

^eWell is monitored continuously by the USGS.

Well-construction data are based upon best available information from well logs, MX Project Report (Ertec Western Inc., 1981), and direct field measurements. Monitoring frequency agreed to by the TRP.



completed for each of the seven SNWA monitor wells included in the network (Eastman, 2007a through g). Copies of the reports have been posted on the SNWA data-exchange web site.

Continuous water-level data were collected at the six designated monitor wells within the network. Site visits were conducted approximately every 6 weeks to obtain periodic water-level measurements and download continuous data for processing and analysis. Physical measurements of water levels were compared to pressure transducer data to ensure proper function and calibration of the instrumentation.

The USGS collects continuous data at two USGS-MX wells within the network 372639114520901 USGS-MX (Delamar Well) and 380531114534201 USGS-MX (N. Dry Lake). Also, the USGS collects continuous data at 374215114453101 USGS-MX (S. Dry Lake Well), which is not included in the network.

Periodic water-level measurements collected by SNWA in 2013 are presented in Appendix A. Historical and 2013 hydrographs for the nine existing DDC network wells that are monitored quarterly are also presented in Appendix A. Water-level data collected by SNWA and USGS at the six continuously monitored network wells are presented in Appendix B. Appendix B also includes tables presenting periodic and daily mean continuous water-level data as well as associated 2013 and historical hydrographs. Historical USGS data are presented at the National Water Information System’s website at <http://waterdata.usgs.gov/nv/nwis/gw>.

2.2.2 Future Monitor Wells

The installation of four future monitor wells is included in the monitoring plan. In 2009, three primary sites and one contingency site were selected by the TRP and NSE for the installation of three of the monitor wells. The location of the fourth well will be selected after additional baseline data are collected and information is known regarding future production-well locations. Location coordinates of future monitor wells, estimated surface elevation and depth to groundwater are presented in Table 2-2. The future monitor-well location sites are presented in Figure 2-1.

**Table 2-2
Future DDC Monitor Wells**

Well Name	Location ^a		Estimated Surface Elevation (ft amsl)	Estimated Depth to Water (ft)
	UTM Northing (m)	UTM Easting (m)		
WRV1012M	4,257,087	675,519	5,794	420
PAH1010M	4,163,098	663,576	4,380	700
DEL4003X	4,125,223	682,153	4,738	1,450
PAH1011M (alternate site)	4,121,019	677,508	3,727	635

^aAll coordinates are Universal Transverse Mercator, North American Datum, 1983, Zone 11.

The northernmost future monitor well, WRV1012M, is located on the west side of the Egan Range northeast of Flag Springs in White River Valley. This well is anticipated to be completed in the Ely Springs Dolomite. The location was selected as a monitoring point between Flag Springs and southern Cave Valley. The new well and other existing monitor wells in Cave Valley will provide baseline water-level data to assist in the evaluation of the hydraulic gradient through Shingle Pass. The depth to groundwater is estimated to be approximately 420 ft bgs at this location.

The second future monitor well, PAH1010M, is located on the east side of the Hiko Range in Sixmile Flat in Pahranaagat Valley. The site is located 3.5 mi east of Hiko Spring. The target completion zone is saturated fractured carbonate rocks within the middle to lower units of the Guilmette Formation and possibly the Simonson Dolomite. Carbonate bedrock is anticipated to be encountered within 50 ft of land surface, and it is expected that rocks will be fractured at depth because of the movement along the range-front fault and ancillary normal faults. The depth to water in this area is estimated to be approximately 700 ft bgs.

Both WRV1012M and PAH1010M are located on BLM managed land, and right-of-way applications have been approved.

The third future monitor well will be installed at the well site of a proposed SNWA exploratory well, DEL4003X, which is located near the southern boundary of Delamar Valley within a structural feature of the Pahranaagat Shear Zone. This well is anticipated to be completed in volcanic materials. An alternative site, PAH1011M, was identified and is also located along a major structural feature of the Pahranaagat Shear Zone but southwest of the exploratory well site. The right-of-way applications have been approved by BLM for both locations. Selection of the primary or alternative site for a monitor well will be determined in consensus with the TRP.

2.2.3 Exploratory- and Production-Well Monitoring

The exploratory-and production-well monitoring section of the DDCMM Plan states that SNWA shall record discharge and water levels in all completed SNWA production wells on a continuous basis. SNWA has not constructed any production wells associated with this project; however, continuous measurements will be collected from all future production wells. Water-level measurements are required in all SNWA exploratory wells at least quarterly.

Water-level data were collected quarterly from two SNWA exploratory and test wells. The wells, one 6-in.-diameter monitor well (CAV6002M2), and one 20-in.-diameter test well (CAV6002X) were installed in southern Cave Valley near Monitor Well 180W902M on October 13 and 28, 2007, respectively. Well-construction attributes and the locations of the two wells are presented in [Table 2-3](#) and [Figure 2-2](#).

Water-level measurements were regularly collected from the wells in accordance with SNWA field operating procedures. Periodic water-level data and the associated hydrographs from the test and exploratory wells are presented in [Appendix C](#).



**Table 2-3
SNWA DDC Exploratory Wells**

Site Number	Station Local Number ^b	Location ^a		Surface ^c Elevation (ft amsl)	Completion Date	Drill Depth (ft bgs)	Well Depth (ft bgs)	Well Casing Diameter (in.)	Screened Interval (ft bgs)	Open Interval (ft bgs)	Aquifer	Monitor Frequency
		UTM Northing (m)	UTM Easting (m)									
CAV6002X	180 N06 E64 19DABB1	4,248,307.58	689,819.01	5,987.97	10/28/2007	917	901	20	219-901	50-917	Carbonate	Quarterly
CAV6002M2	180 N06 E64 19ACDD1	4,248,365.83	689,782.96	5,982.81	10/13/2007	893	885	6	159-882	50-893	Carbonate	Quarterly

^aProfessional survey complete on location and elevation. All coordinates are Universal Transverse Mercator, North American Datum, 1983, Zone 11.

^bStation Local Numbers provided by the Nevada Division of Water Resources.

^cElevations are North American Vertical Datum of 1988 (NAVD88).




Figure 2-2
SNWA DDC Exploratory Wells



2.2.4 Aquifer Testing

A constant-rate pumping test will be performed on each future production well to evaluate aquifer properties. Aquifer-testing results would be used to assess well performance, provide aquifer-property data and assist in evaluating potential future pumping effects. Well-performance step tests and 72-hour constant-rate tests have been performed on SNWA Test Well CAV6002X and Monitor Well 180W902M located in Cave Valley. A summary and results of the tests are presented in *Hydrologic Data Analysis Report for Test Well CAV6002X in Cave Valley Hydrographic Area 180* (Prieur et al., 2011).

2.3 Spring Monitoring Network

The DDCMM Plan spring monitoring network has two components each of which were implemented in 2009. The first component consists of nine springs in White River and Pahranaagat valleys that are monitored for discharge. The second component consists of eight springs within DDC that are monitored biannually for discharge (if measurable), field water-quality parameters, and general physical conditions. The spring locations and monitoring frequency are listed in [Table 2-4](#) and presented in [Figure 2-3](#). Photos of all spring locations and detailed descriptions were presented in SNWA (2009b). A description of each spring and corresponding discharge data are presented in this section.

2.3.1 White River and Pahranaagat Valleys Springs

Nine springs located in White River and Pahranaagat valleys are included in the spring monitoring network. Hot Creek, Ash, and Crystal springs are currently being monitored continuously through a joint funding agreement (JFA) between SNWA, USGS, and the Nevada Division of Water Resources (NDWR). USGS also measures discharge biannually at Flag Springs and Moorman Spring as part of the JFA.

SNWA established spring discharge monitoring sites at Hardy and Hiko springs in 2009. SNWA and NSE staff worked together to secure property access to install the flume at Hardy Springs, and a flow meter and data logger at Hiko Spring. The flow meter provides continuous discharge data on the agricultural diversion pipeline to which Hiko Spring is diverted.

SNWA coordinated with the Nevada Department of Wildlife (NDOW) to install a flume and continuous-monitoring instrumentation at Flag Spring 2 (Middle Flag Spring) in 2009. Flag Spring 1 and 3 continue to be measured at least quarterly by SNWA and biannually by USGS.

Maynard Spring is monitored quarterly by SNWA. SNWA will document conditions at this site dependent upon continued property access. Cottonwood Spring is monitored by USFWS, however no known data was available to be included in the report. Any future data provided USFWS will be included in future annual data reports.

**Table 2-4
DDC Springs Monitoring Locations and Monitoring Frequency**

Basin Number	Station Number	Station Name	Elevation ^a	Location ^b		Monitoring Frequency
				UTM Northing (m)	UTM Easting (m)	
180	1800101	Cave Spring	6,490	4,279,249	691,760	Biannual
	1800301	Parker Station Spring	6,490	4,282,096	688,179	
	381624114540302	USBLM Silver King Well	6,230	4,238,220	683,551	
	381943114562201	Lewis Well	6,260	4,244,297	680,106	
181	1810301	Littlefield Spring	6,150	4,233,949	701,112	Biannual
	1810401	Coyote Spring	5,220	4,211,513	687,693	
	1810501	Big Mud Springs	6,430	4,241,387	689,547	
182	1820101	Grassy Spring	5,790	4,157,193	695,124	
207	2070501	Hot Creek Spring near Sunnyside, NV	5,230	4,249,926	661,290	Continuous
	2071101	Moorman Spring	5,300	4,273,440	662,053	Biannual
	2071501	Hardy Springs	5,350	4,278,196	667,553	
209	2090101	Hiko Spring	3,880	4,162,744	657,549	Continuous
	2090201	Cottonwood Spring	3,240	4,123,643	667,261	Quarterly ^c
	2090801	Maynard Spring	3,110	4,117,909	674,444	Biannual ^d
Flag Springs						
207	2071301	Flag Spring 3 (South)	5,290	4,254,416	672,579	Quarterly
	2071302	Flag Spring 2 (Middle)	5,280	4,254,570	672,576	Continuous
	2071303	Flag Spring 1 (North)	5,290	4,254,696	672,719	Quarterly
Crystal Springs						
209	09415589	Crystal Springs Diversion near Hiko, NV	3,820	4,155,336	656,011	Continuous
	2090401	Crystal Springs near Hiko, NV	3,800	4,155,348	656,165	
Ash Springs						
209	09415639	Ash Springs Diversion at Ash Springs, NV	3,600	4,147,415	659,716	Continuous
	2090501	Ash Springs	3,600	4,147,460	659,684	

^aAll elevations are rounded to the nearest 10 ft, North American Vertical Datum, 1988 (NAVD88). High-resolution Global Positioning System (GPS) will be used to determine elevations at a later date.

^bAll coordinates are Universal Transverse Mercator, North American Datum, 1983 (NAD83) Zone 11.

^cMonitoring performed by USFWS and data to be provided to SNWA and presented in the annual data report.

^dMonitoring frequency will be increased to quarterly after monitoring points are established in consultation with USFWS and BLM.

2.3.1.1 Flag Springs

The Flag Springs are located in Nye County at the NDOW Headquarters for the Wayne Kirsch Wildlife Management Area approximately 60 mi south of Ely, Nevada, along Nevada State Route (SR) 318 (Figure 2-3). Three primary springs (South, Middle, and North) compose the Flag Spring complex which forms the headwaters of Sunnyside Creek at the NDOW headquarters in White River Valley. Sunnyside Creek flows into the Adams-McGill Reservoir where the water is used for livestock, wildlife, and recreation.

Monitoring at Flag Springs currently consists of continuous monitoring of Flag Spring 2 (Middle Flag Spring), which was installed through a cooperative project with NDOW and SNWA, in November




Figure 2-3
Locations of Springs Associated with the DDCMM Plan

2009, and monitoring of Flag Spring 1 and 3 (North and South Flag Spring) orifices at least quarterly by SNWA and twice a year by USGS.

The earliest reported discharge measurement of 2.5 cfs was taken at Flag Spring 1 in 1949 (Maxey and Eakin, 1949). The USGS, beginning in 1982, measured the discharge of the three springs annually. During 1992, the discharge measurements were increased to a biannual frequency that continued through the end of 1994. No discharge measurements were reported between 1995 and 1996. During 1997, the springs were again measured by the USGS biannually, which continued through 2008, as part of the JFA with SNWA and NDWR. Miscellaneous discharge measurements for 2013 and a historical hydrograph are presented in [Appendix D](#). A continuous discharge hydrograph for Flag Spring 2 is also presented in [Appendix D](#).

2.3.1.2 Hardy Springs

Hardy Springs is located approximately 16 mi south of Lund, Nevada, and 1.5 mi west of SR 318 in White River Valley in Nye County ([Figure 2-3](#)). Hardy Springs is composed of five individual spring orifices that discharge into a main channel that is a tributary to the White River. In August 2009, SNWA installed a new flume to obtain biannual discharge measurements upstream of an old diversion approximately 100 to 150 ft downstream of the confluence of Hardy Springs. Hydrologic data collected in 2012 are presented in [Appendix D](#).

The channel between Hardy Springs and the flume was modified by a contractor with permission from the landowner to provide a water source to the power transmission line construction project. A photo of the original condition of the channel and the modified condition with reservoir are presented in [Figures 2-4](#) and [2-5](#), respectively. Discharge measurements performed by SNWA in 2013 used a 3-inch modified Parshall Flume located between the confluence of the five springs and reservoir inlet.

2.3.1.3 Moorman Spring

Moorman Spring is located in White River Valley approximately 20 mi southwest of Lund, Nevada, in Nye County ([Figure 2-3](#)). The spring discharges from the alluvium along a fault scarp. The spring forms a small pool, approximately 30 ft long and 15 to 20 ft wide, behind an old irrigation diversion structure. The discharge at Moorman Spring is currently measured biannually through the JFA.

In 1935, the reported discharge was 0.22 cfs (Stearns et al., 1937). This discharge measurement was likely influenced by the extreme drought in the western United States during the mid-1930s. The same 1935 discharge measurement was again reported in Miller et al. (1953). Since 1935, the average discharge at Moorman Spring has been approximately 0.47 cfs, and the historical discharge measurements appear relatively constant. Discharge data collected at Moorman Spring during 2013 and a hydrograph of the historical data are presented in [Appendix D](#).

2.3.1.4 Hot Creek Spring

Hot Creek Spring is located in southern White River Valley, approximately 36 mi southwest of Lund, Nevada, and 2 mi west of Adams-McGill Reservoir in Nye County ([Figure 2-3](#)). The spring discharge



**Figure 2-4
Hardy Springs Original Condition**



**Figure 2-5
Hardy Springs Modified Condition**

forms Hot Creek, which flows southeast to the Adams-McGill Reservoir. The spring and reservoir are located on the Wayne Kirch Wildlife Management Area, administered by NDOW. At one time, the flow of Hot Creek could be diverted to the Dacey Reservoir to the northeast. Spring discharge is currently being monitored continuously by USGS through the JFA.

A detailed description, site photos, and discussion of historical measurements at Hot Creek Spring are presented in SNWA (2009b). Data collected through 2013, along with historical mean daily discharge data from 2006 to 2013 are provided in [Appendix D](#). Discharge measurements prior to 2006 were measured below the current gage, 50 to 60 ft below the ponded swimming area.

2.3.1.5 Ash Springs

Ash Springs is located in Ash Springs, Nevada, approximately 600 ft east of U.S. Highway 93 (US 93) ([Figure 2-3](#)). The spring is used for irrigation, domestic supply, and recreation and is composed of many orifices that extend more than a quarter mile along the north-south-trending Hiko Fault. The spring area was developed in the 1970s and through the 1980s as a privately owned resort. The main orifice is on public land administered by the BLM and has a large picnic area and swimming pool. Ash Springs discharge and irrigation diversion are currently measured by the USGS using two gaging stations which are funded through the JFA. The two stations were relocated by the USGS during 2011.

A detailed description, photos, and discussion of historical data collected at Ash Springs are presented in SNWA (2009b). Hydrologic data collected through the 2013 water year, historical mean daily discharge, and a 30-day moving average of mean daily discharge values for Ash Springs are presented in [Appendix D](#).

2.3.1.6 Crystal Springs

Crystal Springs is located approximately a quarter mile west of the SR 318/SR 375 junction and a half mile west of the US 93/SR 318 junction in Lincoln County. Crystal Springs is approximately 4 mi south of Hiko, Nevada, and 5 mi north of Ash Springs, Nevada ([Figure 2-3](#)). This locale, used as a watering location and campsite, was the principal stopover on the Mormon Trail alternate route (State of Nevada, 2004). The main channel of the spring and irrigation diversion discharge is currently monitored by USGS through the JFA.

A detailed description and photo documentation of Crystal Springs are presented in SNWA (2009b), including a discussion of the historical data collected at the spring complex. Hydrologic data collected through the 2013 water year, historical mean daily discharge, days of diversion, and annual discharge data are presented in [Appendix D](#).

2.3.1.7 Hiko Spring

Hiko Spring is located on the Cannon Ranch approximately a half mile northeast of Hiko, Nevada, in the north end of Pahranaagat Valley ([Figure 2-3](#)) and has historically provided water for various uses.



Hiko Spring discharges from the base of the Hiko Range and currently provides water for domestic, agricultural, and wildlife purposes.

SNWA monitors discharge at Hiko Spring continuously using a flow meter and datalogger installed on the 18-in.-diameter pipe located approximately 0.5 mi southwest of the spring. The monitoring station was constructed in cooperation with the Hiko Spring Irrigation District and the owners of the Cannon and Whipple Ranches. All work was completed June 2009.

The Hiko Irrigation Company uses a perpetual calendar which assigns irrigation times to each of the twelve members of the company. One complete rotation of the 12 users equates to 11.5 days. There are periods during each rotation when water is diverted above the gage. Daily discharge rates vary between 4.3 to 8.3 cfs depending upon the season and irrigation needs of the individual users.

A detailed description and photo documentation of Hiko Spring are presented in SNWA (2009b), including a discussion of the historical data collected at the spring complex. Hydrologic data collected during the 2013 water year and a historical hydrograph are presented in [Appendix D](#).

2.3.1.8 Maynard Spring

Maynard Spring is located off of US 93 about 14 mi southeast of Alamo, Nevada, and 2.5 mi southeast of Lower Pahrangat Lake on BLM land in Pahrangat Valley ([Figure 2-3](#)). The spring is composed of two springheads, referred to as North Maynard Spring and South Maynard Spring, which are separated by a distance of roughly 400 ft. Photos of Maynard Spring in May and October 2013 are presented in [Figures E-1](#) and [E-2](#) of Appendix E. SNWA will continue to coordinate with BLM and USFWS to establish water-level monitoring points at Maynard Spring. Observations in 2013 indicated no measurable discharge.

2.3.1.9 Cottonwood Spring

Cottonwood Spring is approximately 9.5 mi south of Alamo, Nevada, 1 mi west of US 93 on the USFWS Pahrangat Wildlife Refuge ([Figure 2-3](#)), and 1.5 mi south of the Refuge Headquarters along the Corn Creek/Alamo Road. As per Exhibit A of the Stipulation, USFWS is to provide data collected from Cottonwood Spring to the TRP. SNWA will include any discharge measurements collected and provided by USFWS in the annual data report. The water at Cottonwood Spring is used for wildlife. Photo documentation and historical data reported for Cottonwood Spring is presented in SNWA (2009b).

2.3.2 DDC Springs Biannual Monitoring

Eight spring monitoring locations were selected within the DDC valleys by the TRP in consultation with the NSE for biannual monitoring. These springs are generally characterized as being sourced in the mountain block and as having no hydraulic connection to the regional aquifer. However, biannual baseline monitoring is being performed to document variability in spring conditions.

Springs included in the program are Grassy Spring in Delamar Valley; Coyote, Big Mud, and Littlefield springs in Dry Lake; Parker Station and Cave springs in northern Cave Valley; and Lewis Well and Silver King Well in southern Cave Valley. Spring locations are presented in [Figure 2-3](#). Several of the springs (Grassy, Big Mud, Coyote, and Lewis Well) have been modified in the past with a collector system to transmit water to distribution points away from the spring. Silver King Well is a shallow dug well with a gravity discharge line to a stock water area.

Field visits to the sites are conducted in the spring and fall of each year when site-access conditions permit. Wetted area and discharge (if measurable) are documented. Spring water-quality is measured in the field for pH, electrical conductivity, and temperature. Photographs are taken to document site conditions.

Physical descriptions, photos, and historical hydrologic and water-chemistry data for the springs are presented in SNWA (2009b).

A site visit was performed in May and October 2013. Data collected during the visit and photo documentation are presented in [Appendices D](#) and [E](#), respectively.

2.3.2.1 Cave Spring

Cave Spring is located at the far southwest corner of a low northeast-southwest-trending hill approximately 3 mi southeast of Parker Station, Nevada ([Figure 2-3](#)). The decrease in discharge rates during the summer months and the cold temperature of the water indicate that this spring is fed solely by local recharge. Biannual discharge measurements and conditions are being documented at the spring with permission from the owner, Cave Valley Ranch, LLC.

A detailed description and photo documentation of Cave Spring are presented in SNWA (2009b), including a discussion of historical data collected at the spring. Hydrologic data collected during the 2013 are presented in [Appendix D](#). A photo of the spring, taken in May 2013, during usually high discharge is presented in [Figure E-3](#). The photo taken in October 2013 is presented in [Figure E-4](#). Both photos show dry conditions.

Currently, there are no active diversions at the spring. Historically, it appears that a small, hand-dug well was constructed in the stream channel and was used to divert water by pump. The water now flows freely down the channel into a small reservoir in the center of the valley where it is used for livestock watering.

2.3.2.2 Parker Station

Parker Station is in north-central Cave Valley, approximately 16 mi southeast of Lund, Nevada. Parker Station was once used as a stagecoach station. This site is located in Lincoln County, nearly a mile south of the White Pine/Lincoln County line.

Parker Station Spring lies on Cave Valley Ranch, LLC, property. A description of the physical conditions are documented biannually at the flowing well and nearby spring with access permission



from Cave Valley Ranch, LLC. A photo of spring discharge in the Parker Station Area in May and October 2013 are presented in [Figures E-5](#) and [E-6](#), respectively. A photo of a flume near the miscellaneous discharge measurement site is presented in [Figure E-7](#).

2.3.2.3 Lewis Well

The Lewis Well is located in southern Cave Valley, approximately 36 mi south of Lund, Nevada, and 6 mi east of SR 318 ([Figure 2-3](#)). It is located at the base of the Egan Range on the eastern slope. The well was reportedly constructed in 1925 and was completed with a 42-in. steel casing to a depth of 26 ft. Photos of the springhead area for Lewis Well taken in May and October 2013 are presented in [Figures E-8](#) and [E-9](#), respectively. A photo of spring discharge at a manhole access to a collection system near the spring head is presented in [Figure E-10](#).

2.3.2.4 Silver King Well

Silver King Well is a hand-dug well located within Lincoln County, Nevada, in southern Cave Valley as shown in [Figure 2-3](#). The dug well may have been a modification to a historic spring. Water is discharged from the Silver King Well by gravity drainage through approximately 600 ft of 2-in. pipe into a partially buried trough. Photos of the Silver King Well and discharge area are presented in SNWA (2009b). Photos taken May and October 2013 are presented in [Figures E-11](#) and [E-12](#), respectively.

Water-level data collected at the Silver King Well is limited prior to implementation of the SNWA monitoring program with only two records available. A depth-to-water level on March 21, 1990, was reported as 8.90 ft bgs. The second depth-to-water measurement was made on August 25, 2003, and was reported as 7.95 ft bgs. Two depth-to-water measurements were taken in 2012. The first, on May 21, 2013 was 11.62 ft bgs and the second, on October 15, 2013 was 10.23 ft bgs.

2.3.2.5 Coyote Spring

Coyote Spring is located in Dry Lake Valley approximately 8 mi west-southwest of Bristol Wells, Nevada ([Figure 2-3](#)), and lies at the center of an abandoned homestead compound. Two spring orifices exist at the site. Photos of Coyote Spring and the discharge area are presented in SNWA (2009b). Photos taken in May and October 2013 are presented in [Figures E-13](#) and [E-14](#), respectively.

Coyote Spring discharges from the base of an escarpment approximately 15 ft high in volcanic rocks. The spring discharge is collected and piped to a large concrete tank. Discharge from Coyote Spring was measured at 5 gpm in 1912 and at 0.9 gpm in August 1979. On June 3, 2004, discharge was measured at 0.11 gpm. On June 21, 2004, the discharge was 0.02 gpm. Discharge on the May 20, 2013 field visit was 0.64 gpm. There was no discharge observed on October 15, 2013.

2.3.2.6 Big Mud Springs

Big Mud Springs is located in northern Dry Lake Valley as shown in [Figure 2-3](#). The springs are located in the Schell Creek Range along Big Mud Pass approximately 7 mi north of Silver King

Mountain. A wood fence is present at the springs. The area is surrounded by dense vegetation, such as junipers, willows, and wild roses. A collection basin is in place to divert the spring discharge for stock watering.

Photos of Big Mud Springs and water storage tanks are presented in SNWA (2009b). Photos of the springhead taken in May and October 2013 are presented in [Figures E-15](#) and [E-16](#), respectively.

2.3.2.7 Littlefield Spring

Littlefield Spring is located approximately 3 mi south of Meloy Spring on the east side of Dry Lake Valley ([Figure 2-3](#)). Littlefield Spring discharges from the alluvium near an outcrop of volcanic rock. This spring had a reported discharge of 0.02 cfs in May 1980 (Bunch and Harrill, 1984). No diversions exist near the spring. The spring head for Littlefield Spring was restored in 2004. A photo of the spring discharge area taken in May 2013 is presented in [Figure E-17](#). The photo taken in October 2013 of the spring area and discharge measuring point is presented in [Figure E-18](#). Discharge measured on May 20 and October 15, 2013 was 0.03 cfs.

2.3.2.8 Grassy Spring

Grassy Spring is located in Delamar Valley approximately 40 mi south of Bristol Wells, Nevada, along the western flank of the Delamar Mountains ([Figure 2-3](#)). Photos of Grassy Spring taken in May and October 2013 are presented in [Figures E-19](#) and [E-20](#). Grassy Spring is currently used for stock watering. The discharge is captured at the source and is transferred to livestock-watering tanks through black polyvinyl tubing.

The spring discharges from alluvial sediments in close contact with volcanic rocks. The discharge was measured volumetrically at the livestock tank, approximately 300 ft west of the spring. The site was dry during the field visit on May 20, 2013. On October 15, 2013, there was some water in the Grassy Spring stock storage tank; however, there was no measurable discharge.

2.4 Precipitation-Station Network

Precipitation-station data from selected network sites which are currently operating and have an established historical record in the vicinity of the study area were compiled and are presented in [Appendix F](#). The precipitation network will assist in assessing climate variability in the vicinity of the project basins and discerning pumping effects from natural variability. The precipitation network stations are listed in [Table 2-5](#) and are presented on [Figure 2-6](#).



**Table 2-5
DDC Precipitation-Station Locations**

Station Number	Station Name	Location ^a		Surface Elevation ^b (ft amsl)	Data Source
		UTM Northing (m)	UTM Easting (m)		
RP1830101	Mount Wilson (NDWR)	4,254,245	731,613	7,370	NDWR
RP1730201	Blue Eagle Ranch Hanks	4,264,579	626,889	4,780	WRCC
RP1790202	McGill	4,365,043	691,693	6,270	WRCC
RP2010201	Spring Valley State Park	4,214,070	747,476	5,950	WRCC
RP2020201	Pioche	4,201,608	724,101	5,990	WRCC
RP2050201	Caliente	4,166,217	719,251	4,400	WRCC
RP2050202	Elgin	4,136,286	717,627	3,420	WRCC
RP2070201	Sunnyside	4,254,668	672,599	5,297	WRCC
RP2070202	Lund	4,303,974	672,091	5,546	WRCC
RP2090201	Hiko	4,158,266	656,900	3,900	WRCC
RP2090202	Pahranagat Wildlife Refuge	4,126,390	666,716	3,400	WRCC
RP2070301	Ward Mountain	4,333,574	677,187	9,200	NRCS (SnoTel)
RP1730401	Quinn Canyon Range	4,228,799	620,297	9,050	USGS
RP1820401	Unnamed Peak South of Chokecherry Peak	4,154,830	700,904	7,800	USGS
RP1820402	Unnamed Peak in South Delamar Mountains	4,135,352	701,473	7,800	USGS
RP1830401	Mount Wilson (USGS)	4,236,084	728,118	9,200	USGS
RP1840401	Mount Washington	4,309,377	732,764	10,440	USGS
RP1840402	Cave Mountain	4,337,545	706,107	10,650	USGS
RP2030401	Highland Peak	4,196,772	712,963	9,330	USGS
RP2090401	Mount Irish	4,168,657	641,846	8,607	USGS

^aAll coordinates in Universal Transverse Mercator, North American Datum, 1983 (NAD83), Zone 11.

^bElevations are North American Vertical Datum, 1988 (NAVD88).

The precipitation-station network includes the following:

- One high-altitude precipitation station operated by NDWR located in the Wilson Creek Range.
- Eight high-altitude precipitation stations maintained and operated by USGS through a JFA with SNWA and NDWR.
- Ten National Oceanic and Atmospheric Administration, National Weather Service (NOAA/NWS) Stations. Data were obtained through the Western Regional Climate Center (WRCC).




Figure 2-6
DDC Precipitation-Station Locations



- One U.S. Department of Agriculture (USDA) Natural Resources Conservation Service (NRCS) SNOwpack TELemetry (SNOTEL) site located in the Egan Range. This site provides precipitation and snow-accumulation data.

Provisional 2013 precipitation data for the stations, along with historical data and statistics, are presented in [Appendix F](#). USGS data from seven of the eight high altitude precipitation station were unavailable as of time of report publication. SNWA will continue to compile and report precipitation data from these sites as long as the data are made available and the stations are in operation.

Data sources for precipitation information presented in this report are as follows:

- NDWR data is cited from Nevada Division of Water Resources (NDWR, 2014)
- USGS data is cited from USGS National Water Information System (USGS, 2014)
- SNOTEL data is cited from USDA Natural Resources Conservation Service (USDA, 2014)
- National Weather Service data is cited from Western Regional Climate Center (WRCC, 2014)

2.5 Water Chemistry

A summary of water-chemistry results from program wells and springs of the DDC monitoring network were presented in SNWA (2009b). The results were derived from samples collected by SNWA, USGS, and Desert Research Institute as well as those reported in historical reports dating as far back as 1912 (Carpenter, 1915). On July 2, 2009, water samples were collected from Hiko and Hardy springs and analyzed for a suite of chemical constituents. The results for these samples were presented in SNWA, 2010.

Spring field measurements of the water-quality parameters were performed using SNWA and the National Field Manual for the Collection of Water-Quality Data (USGS, 2008) procedures. All measurement equipment was calibrated according to the manufacturer calibration procedures.

On March 31, 2010 the TRP held a conference call to discuss the water-chemistry sampling programs required by the DDCMM Plan. The TRP recommended to the EC that the water-chemistry sampling program be postponed and implemented after the three future monitor wells specified in the DDCMM Plan have been installed. The EC approved the TRP recommendation. Implementation of the program will include collection of two rounds of water-chemistry samples six months apart at 10 locations selected by the TRP. SNWA will collect and submit samples for chemical analysis for the water-chemistry parameters listed in [Table 2-6](#). Subsequent sampling will be performed once every 5 years following the start of SNWA groundwater production.

2.6 Data Reporting

A data-exchange web site accessible by the NSE, EC, TRP, and BRT members was created in April 2008. The data-exchange web site is used to distribute SVMM Plan monitoring data to the TRP within 90 days of collection. Data is also submitted directly to the NSE on a quarterly basis in electronic format.

**Table 2-6
Water-Chemistry Parameters**

Field Parameters	Major Ions	Isotopes	Minor and Trace Elements
Water temperature	TDS	Oxygen-18	Arsenic
Air temperature	Calcium	Deuterium	Barium
pH	Sodium	Tritium	Cadmium
Electrical conductivity	Potassium	Chlorine-36 ^a	Chromium
Dissolved oxygen	Chloride	Carbon-14 ^a	Lead
	Bromide	Carbon-13 ^a	Mercury
	Fluoride	Strontium-87 ^a	Selenium
	Nitrate	Uranium-238 ^a	Silver
	Phosphate		Manganese
	Sulfate		Aluminum
	Alkalinity		Iron
	Silica		Bromide
	Magnesium		Fluoride

^aThese parameters shall be included only in the first sampling event and shall not be included in any further water-chemistry sampling performed pursuant to this plan.

A data and status report is submitted annually to the TRP and NSE.

2.7 Proposed Schedule of Groundwater Withdrawals

No groundwater production is scheduled for the next two years with the exception of possible short-term development, well-performance testing, and aquifer testing of any new wells drilled during this time-frame. The duration of well-performance testing is typically one day. The duration of the constant-rate aquifer testing is typically under one week.



This Page Left Intentionally Blank

3.0 ANTICIPATED 2014 SNWA DDCMM PLAN ACTIVITIES

Anticipated DDCMM Plan-related activities in 2014 are summarized below.

- Continue to collect required quarterly and continuous water-level and spring discharge measurements at program sites throughout 2014.
- Coordinate activities and provide technical assistance to the BRT if requested.
- Report data quarterly to other TRP members through the SNWA data-exchange web site. Data will also be submitted to NSE in an approved electronic format and included in the annual data report to be submitted in March 2015.

SNWA will continue to work with the NSE and the other members of the TRP participants to implement the DDCMM Plan and identify and address technical issues related to the program.



This Page Left Intentionally Blank

4.0 REFERENCES

- Bunch, R.L., and Harrill, J.R., 1984, Compilation of selected hydrologic data from the MX missile-siting investigation, east-central Nevada and western Utah: U.S. Geological Survey Open-File Report 84-702, 123 p.
- Carpenter, E., 1915, Ground water in southeastern Nevada: U.S. Geological Survey Water-Supply Paper 365, 86 p.
- Eastman, H.S., 2007a, Geologic data analysis report for Monitor Well 180W501M in Cave Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0004, 29 p.
- Eastman, H.S., 2007b, Geologic data analysis report for Monitor Well 180W902M in Cave Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0003, 31 p.
- Eastman, H.S., 2007c, Geologic data analysis report for Monitor Well 181M-1 in Dry Lake Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0005, 28 p.
- Eastman, H.S., 2007d, Geologic data analysis report for Monitor Well 181W909M in Dry Lake Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0007, 30 p.
- Eastman, H.S., 2007e, Geologic data analysis report for Monitor Well 182M-1 in Delamar Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0002, 29 p.
- Eastman, H.S., 2007f, Geologic data analysis report for Monitor Well 182W906M in Delamar Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0001, 30 p.
- Eastman, H.S., 2007g, Geologic data analysis report for Monitor Well 209M-1 in Pahrnagat Valley: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. RDS-ED-0006, 29 p.
- Ertec Western, Inc., 1981, MX Siting Investigation—Geotechnical Evaluation—Verification Study—Cave Valley, Nevada, Volume II: Ertec Western, Inc., Long Beach, California, Report E-TR-27-CV-II, 102 p.
- Maxey, G.B., and Eakin, T.E., 1949, Ground water in White River Valley, White Pine, Nye, and Lincoln counties, Nevada: State of Nevada, Office of the State Engineer, Water Resources Bulletin No. 8, 59 p.
- Miller, M.R., Hardman, G., and Mason, H.G., 1953, Irrigation waters of Nevada: University of Nevada, Reno, Agricultural Experiment Station Bulletin No. 187, 63 p.



NSC, see Nevada Supreme Court

Nevada Supreme Court, 2010, *Great Basin Water Network v. State Engineer*, 126 Nev., Ad. Op. No. 20, June 17, 2010.

Prieur, J.P., Acheampong, S.Y., Ashinhurst, C.S., and Fryer, W., 2011, *Hydrologic data analysis report for Test Well CAV6002X in Cave Valley Hydrographic Area 180*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. DAR-ED-0008, 95 p.

SNWA, see Southern Nevada Water Authority.

Southern Nevada Water Authority, 2008, *Delamar, Dry Lake, and Cave Valley stipulation agreement hydrologic monitoring plan status and data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0002, 31 p.

Southern Nevada Water Authority, 2009a, *Hydrologic monitoring and mitigation plan for Delamar, Dry Lake, and Cave valleys*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0006, 38 p.

Southern Nevada Water Authority, 2009b, *Delamar, Dry Lake, and Cave valleys stipulation agreement hydrologic monitoring plan status and historical data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0005, 162 p.

Southern Nevada Water Authority, 2010, *2009 Delamar, Dry Lake, and Cave Valleys hydrologic monitoring and mitigation plan status and data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0008, 117 p.

Southern Nevada Water Authority, 2011a, *Hydrologic monitoring and mitigation plan for Delamar, Dry Lake, and Cave valleys*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0011, 44 p.

Southern Nevada Water Authority, 2011b, *2010 Delamar, Dry Lake, and Cave Valleys hydrologic monitoring and mitigation plan status and data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0009, 116 p.

Southern Nevada Water Authority, 2012, *2011 Delamar, Dry Lake, and Cave Valleys hydrologic monitoring, management, and mitigation plan status and data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0013, 108 p.

Southern Nevada Water Authority, 2013, *2012 Delamar, Dry Lake, and Cave Valleys hydrologic monitoring, management, and mitigation plan status and data report*: Southern Nevada Water Authority, Las Vegas, Nevada, Doc. No. WRD-ED-0018, 106 p.

State of Nevada, 2004, *Department of Cultural Affairs, State Historic Preservation Office, Nevada, Crystal Springs–Historical Marker 205* [Internet], [accessed July 14, 2005], available from <http://nvshpo.org>.

Stearns, N.D., Stearns, H.T., and Waring, G.A., 1937, Thermal springs in the United States: U.S. Geological Survey Water-Supply Paper 679-B, 206 p.

Stipulation for Withdrawal of Protests: U.S. Bureau of Indian Affairs, U.S. Bureau of Land Management, U.S. Fish and Wildlife Service, National Park Service, Southern Nevada Water Authority. (Jan. 7, 2008).

USDA, see U.S. Department of Agriculture.

U.S. Department of Agriculture, 2012, Natural Resources Center Service (NRCS) National Water & Climate Center (WCC) [Internet], [accessed January 2014], available from <http://www.wcc.nrcs.usda.gov>.

U.S. Geological Survey, 2008, National field manual for the collection of water-quality data, U.S. Geological Survey Techniques of Water-Resources Investigations, Book 9, chaps. A1-A9, available from <http://pubs.water.usgs.gov/twri9A>.

U.S. Geological Survey, 2014, National Water Information System (NWIS Web) [Internet], [accessed February 25, 2014], available from <http://waterdata.usgs.gov/nwis>.

USGS, see U.S. Geological Survey.

Western Regional Climate Center (WRCC), 2014, Historical Climate Information [Internet], [accessed January 2014], available from <http://www.wrcc.dri.edu>.

WRCC, see Western Regional Climate Center.



This Page Left Intentionally Blank

Appendix A

Periodic Water-Level Measurement Data from the DDC Existing-Well Monitoring Network

Table A-1
Periodic Water-Level Measurement Data from the DDC
Existing-Well Monitoring Network
 (Page 1 of 3)

Site Number	Station Local Number ^a	Well Depth (ft bgs)	Surface ^b Elevation (ft amsl)	Water Level			
				Date	Depth to Water (ft bgs)	Well Status ^c	Measurement Method ^d
180W902M ^e	180 N06 E64 19ADCC1	903	5,984.89	1/7/2013	142.50	S	T
				2/11/2013	142.86	S	T
				4/1/2013	142.80	S	T
				5/6/2013	142.92	S	T
				7/8/2013	143.08	S	T
				8/27/2013	142.96	S	T
				10/7/2013	142.97	S	T
				11/20/2013	143.06	S	T
382807114521001	180 N07 E63 14BADD 1	460	6,012.39	5/6/2013	217.11	S	T
				8/27/2013	217.04	S	T
				11/20/2013	217.00	S	T
383307114471001	180 N08 E64 15BCBC1	---	6,162.55	2/11/2013	262.60	S	T
				5/6/2013	262.54	S	T
				8/27/2013	262.63	S	T
				11/20/2013	262.68	S	T
180W501M ^e	180 N09 E64 31CBBD1	1,212	6,428.63	1/7/2013	1057.31	S	T
				2/11/2013	1057.46	S	T
				4/1/2013	1057.41	S	T
				5/6/2013	1057.53	S	T
				7/8/2013	1057.60	S	T
				8/27/2013	1057.82	S	T
				10/7/2013	1057.81	S	T
				11/20/2013	1058.03	S	T
182W906M	182 S07 E64 19ACDB1	1,703	4,796.96	1/9/2013	1316.55	S	T
				2/13/2013	1316.82	S	T
				4/1/2013	1316.15	S	T
				5/7/2013	1316.18	S	T
				7/8/2013	1316.38	S	T
				8/26/2013	1316.43	S	T
				11/20/2013	1316.02	S	T
182M-1 ^e	182 S07 E63 18AAAA1	1,321	4,597.78	1/10/2013	826.81	S	T
				2/13/2013	827.13	S	T
				4/1/2013	827.06	S	T
				5/7/2013	827.15	S	T
				7/8/2013	827.12	S	T
				8/26/2013	827.09	S	T
				10/7/2013	827.00	S	T
				11/20/2013	826.95	S	T



Table A-1
Periodic Water-Level Measurement Data from the DDC
Existing-Well Monitoring Network
 (Page 2 of 3)

Site Number	Station Local Number ^a	Well Depth (ft bgs)	Surface ^b Elevation (ft amsl)	Water Level			
				Date	Depth to Water (ft bgs)	Well Status ^c	Measurement Method ^d
181W909M	181 S03 E65 07CCDA1	1,260	4,799.41	1/7/2013	498.10	S	T
				2/12/2013	498.20	S	T
				4/1/2013	498.03	S	T
				5/7/2013	498.11	S	T
				7/8/2013	498.18	S	T
				8/26/2013	498.26	S	T
				11/19/2013	498.15	S	T
181M-1 ^e	181 N01 E63 36ABAA1	1,472	4,963.07	1/7/2013	675.16	S	T
				2/11/2013	675.23	S	T
				4/1/2013	675.16	S	T
				7/8/2013	675.15	S	T
				8/26/2013	675.20	S	T
				10/7/2013	675.08	S	T
				11/19/2013	675.03	S	T
380531114534201 ^e	181 N03 E63 27CAA 1	2,395	5,456.35	2/11/2013	844.96	S	T
				5/6/2013	844.48	S	T
				8/26/2013	844.89	S	T
				11/19/2013	844.68	S	T
209 S07 E62 20AA 1	209 S07 E62 20AA 1	695	4,082.46	2/13/2013	600.09	S	T
				5/7/2013	600.14	S	T
				8/29/2013	600.44	S	T
				11/20/2013	600.06	S	T
373405115090001	209 S04 E61 28CD 1	980	4,230.58	2/13/2013	586.50	S	T
				5/7/2013	586.32	S	T
				8/29/2013	586.77	S	T
				11/20/2013	586.39	S	T
373803115050501	209 S04 E61 01AACB1	700	4,528.90	2/13/2013	785.81	S	T
				5/7/2013	785.45	S	T
				8/27/2013	784.37	S	T
				11/20/2013	785.20	S	T
209M-1 ^e	209 S03 E62 35DAAD1	1,616	5,097.30	1/7/2013	1200.09	S	T
				2/13/2013	1200.29	S	T
				4/1/2013	1200.01	S	T
				5/7/2013	1200.06	S	T
				7/8/2013	1200.23	S	T
				8/27/2013	1200.10	S	T
				10/7/2013	1200.15	S	T
11/19/2013	1200.00	S	T				

Table A-1
Periodic Water-Level Measurement Data from the DDC
Existing-Well Monitoring Network
 (Page 3 of 3)

Site Number	Station Local Number ^a	Well Depth (ft bgs)	Surface ^b Elevation (ft amsl)	Water Level			
				Date	Depth to Water (ft bgs)	Well Status ^c	Measurement Method ^d
383133115030201	207 N08 E62 30CD 1	101	5,290.20	2/11/2013	64.36	S	T
				5/6/2013	64.27	S	T
				8/26/2013	64.31	S	T
				11/18/2013	64.40	S	T
372639114520901	182 S06 E63 12AD 1	1,195	4,706.30	2/13/2013	863.55	S	T
				5/7/2013	863.41	S	T
				8/26/2013	863.59	S	T
				11/20/2013	863.22	S	T

^aStation Local Numbers provided by the Nevada Division of Water Resources.



^bElevations are North American Vertical Datum of 1988 (NAVD88).

^cS = Static conditions, P = Pumping



^dT = Electric tape measurement



^eCurrent year and historical hydrographs with periodic and continuous data are presented in [Appendix B](#).

Note: SNWA tape calibration program started in August 2008.







2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report









2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report









2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report





2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report





Appendix B

Continuous Water-Level Measurement Data from the DDC Existing-Well Monitoring Network

B.1.0 MONITORING PROGRAM WELLS WITH CONTINUOUS TRANSDUCER DATA

Continuous data collection was performed in 2013 for the following monitor wells:

- Cave Valley Well 180W902M
- Cave Valley Well 180W501M
- Delamar Valley Well 182M-1
- Dry Lake Valley Well 181M-1
- Dry Lake Valley Well 380531114534201
- Pahranaagat Valley Well 209M-1

For these sites, two hydrographs are presented that include data collected in 2013 and during the historical period of record. Continuous data have been corrected for temperature and transducer cable stretch. Additional data processing, including barometric pressure, may be applied in the future.



Table B-1
Cave Valley Well 180W902M, Calendar Year 2013
Water-Level Data, Daily Mean Values

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	142.62	142.66	142.74	142.71	142.85	142.81	142.86	142.89	142.95	142.99	143.12	143.16
2	142.60	142.67	142.67	142.73	142.85	142.78	142.86	142.90	142.96	142.97	143.04	143.07
3	142.62	142.62	142.60	142.74	142.73	142.80	142.86	142.91	142.97	143.01	143.02	142.95
4	142.61	142.63	142.68	142.72	142.69	142.80	142.85	142.91	142.97	143.08	143.05	143.10
5	142.62	142.59	142.64	142.72	142.70	142.83	142.85	142.90	142.96	143.09	143.12	143.11
6	142.55	142.62	142.59	142.72	142.75	142.83	142.86	142.91	142.97	143.04	143.14	143.13
7	142.59	142.58	142.61	142.66	142.76	142.82	142.88	142.91	142.97	142.98	143.08	143.04
8	142.62	142.49	142.56	142.59	142.76	142.82	142.88	142.91	142.95	142.94	143.07	143.16
9	142.56	142.58	142.69	142.74	142.78	142.83	142.90	142.91	142.93	142.90	143.10	143.24
10	142.42	142.61	142.74	142.76	142.81	142.81	142.88	142.93	142.96	142.97	143.13	143.18
11	142.54	142.66	142.71	142.73	142.83	142.82	142.86	142.94	142.97	143.02	143.14	143.21
12	142.58	142.69	142.71	142.73	142.82	142.83	142.87	142.93	142.96	143.00	143.16	143.18
13	142.59	142.67	142.74	142.67	142.79	142.82	142.89	142.93	142.96	143.01	143.10	143.17
14	142.64	142.69	142.72	142.69	142.76	142.83	142.88	142.94	142.96	143.06	143.03	143.24
15	142.68	142.72	142.68	142.65	142.75	142.83	142.87	142.94	142.97	143.05	142.96	143.21
16	142.67	142.66	142.64	142.74	142.73	142.84	142.88	142.94	142.97	143.06	142.98	143.19
17	142.64	142.57	142.66	142.79	142.75	142.84	142.90	142.94	142.93	143.04	143.12	143.18
18	142.64	142.62	142.69	142.82	142.78	142.79	142.89	142.95	142.96	143.07	143.11	143.09
19	142.65	142.48	142.70	142.74	142.79	142.83	142.88	142.95	142.99	143.06	143.06	143.02
20	142.63	142.53	142.65	142.76	142.79	142.83	142.87	142.94	142.97	143.03	143.04	143.10
21	142.63	142.63	142.65	142.75	142.74	142.83	142.88	142.94	142.91	143.07	143.09	143.12
22	142.63	142.68	142.64	142.74	142.69	142.84	142.89	142.95	142.96	143.06	143.10	143.22
23	142.62	142.63	142.71	142.77	142.76	142.81	142.91	142.93	143.02	143.05	143.11	143.23
24	142.62	142.68	142.70	142.76	142.80	142.82	142.89	142.94	142.95	143.05	143.13	143.22
25	142.61	142.66	142.69	142.75	142.77	142.86	142.91	142.95	142.88	143.09	143.17	143.24
26	142.52	142.68	142.66	142.80	142.78	142.88	142.93	142.97	142.96	143.08	143.16	143.22
27	142.51	142.73	142.69	142.79	142.78	142.92	142.89	142.94	143.03	142.94	143.10	143.20
28	142.59	142.75	142.70	142.76	142.76	142.86	142.89	142.96	143.04	142.94	143.12	143.14
29	142.63	---	142.74	142.73	142.77	142.85	142.91	142.97	143.02	143.04	143.15	143.22
30	142.66	---	142.73	142.71	142.79	142.86	142.92	142.96	143.00	143.08	143.15	143.21
31	142.65	---	142.70	---	142.84	---	142.91	142.95	---	143.10	---	143.19
Max	142.68	142.75	142.74	142.82	142.85	142.92	142.93	142.97	143.04	143.10	143.17	143.24
Min	142.42	142.48	142.56	142.59	142.69	142.78	142.85	142.89	142.88	142.90	142.96	142.95

Year 2013 Statistics: Year Max 143.24; Year Min 142.42

Note: Water level in ft bgs

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report









Table B-2
Cave Valley Well 180W501M, Calendar Year 2013
Water-Level Data, Daily Mean Values

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	1057.23	1057.28	1057.39	1057.35	1057.53	1057.48	1057.60	1057.64	1057.73	1057.75	1057.88	1057.99
2	1057.22	1057.31	1057.31	1057.37	1057.49	1057.45	1057.61	1057.66	1057.73	1057.73	1057.79	1057.86
3	1057.24	1057.25	1057.25	1057.40	1057.40	1057.48	1057.59	1057.68	1057.74	1057.78	1057.82	1057.80
4	1057.23	1057.27	1057.34	1057.34	1057.38	1057.50	1057.58	1057.68	1057.76	1057.84	1057.82	1057.92
5	1057.23	1057.22	1057.28	1057.35	1057.39	1057.53	1057.57	1057.67	1057.74	1057.85	1057.91	1057.89
6	1057.17	1057.27	1057.24	1057.36	1057.41	1057.52	1057.58	1057.67	1057.74	1057.81	1057.93	1057.89
7	1057.24	1057.20	1057.26	1057.31	1057.40	1057.52	1057.60	1057.68	1057.73	1057.76	1057.87	1057.80
8	1057.26	1057.12	1057.20	1057.24	1057.44	1057.52	1057.62	1057.66	1057.71	1057.72	1057.87	1057.95
9	1057.16	1057.21	1057.34	1057.38	1057.45	1057.52	1057.63	1057.67	1057.70	1057.70	1057.91	1058.01
10	1057.07	1057.20	1057.36	1057.37	1057.49	1057.50	1057.61	1057.69	1057.72	1057.75	1057.94	1057.95
11	1057.18	1057.26	1057.33	1057.31	1057.51	1057.54	1057.60	1057.69	1057.72	1057.79	1057.95	1058.01
12	1057.18	1057.29	1057.36	1057.33	1057.50	1057.52	1057.61	1057.70	1057.72	1057.74	1057.96	1057.96
13	1057.19	1057.28	1057.39	1057.28	1057.48	1057.51	1057.63	1057.71	1057.70	1057.77	1057.92	1058.00
14	1057.24	1057.32	1057.36	1057.28	1057.45	1057.54	1057.63	1057.71	1057.70	1057.83	1057.82	1058.07
15	1057.30	1057.34	1057.32	1057.27	1057.44	1057.54	1057.61	1057.71	1057.72	1057.82	1057.81	1058.05
16	1057.30	1057.27	1057.30	1057.34	1057.40	1057.56	1057.62	1057.72	1057.72	1057.83	1057.80	1058.05
17	1057.30	1057.21	1057.31	1057.39	1057.43	1057.54	1057.67	1057.71	1057.67	1057.82	1057.93	1058.02
18	1057.29	1057.25	1057.34	1057.42	1057.46	1057.48	1057.65	1057.73	1057.72	1057.86	1057.87	1057.94
19	1057.31	1057.13	1057.34	1057.39	1057.47	1057.53	1057.64	1057.71	1057.74	1057.85	1057.85	1057.90
20	1057.30	1057.19	1057.27	1057.41	1057.48	1057.53	1057.62	1057.71	1057.71	1057.82	1057.83	1057.94
21	1057.31	1057.25	1057.29	1057.41	1057.41	1057.53	1057.63	1057.72	1057.64	1057.88	1057.88	1057.95
22	1057.30	1057.25	1057.27	1057.39	1057.37	1057.54	1057.65	1057.72	1057.70	1057.86	1057.91	1058.03
23	1057.29	1057.22	1057.35	1057.42	1057.42	1057.49	1057.65	1057.70	1057.76	1057.85	1057.90	1058.05
24	1057.29	1057.30	1057.33	1057.42	1057.45	1057.52	1057.65	1057.72	1057.67	1057.86	1057.92	1058.04
25	1057.27	1057.27	1057.32	1057.40	1057.44	1057.57	1057.66	1057.73	1057.62	1057.89	1057.97	1058.08
26	1057.19	1057.31	1057.29	1057.48	1057.45	1057.59	1057.69	1057.73	1057.69	1057.88	1057.97	1058.07
27	1057.18	1057.34	1057.33	1057.45	1057.44	1057.61	1057.64	1057.72	1057.77	1057.72	1057.91	1058.04
28	1057.22	1057.36	1057.34	1057.42	1057.43	1057.60	1057.63	1057.73	1057.77	1057.79	1057.93	1057.99
29	1057.23	---	1057.38	1057.38	1057.42	1057.59	1057.67	1057.75	1057.76	1057.81	1057.98	1058.08
30	1057.29	---	1057.37	1057.37	1057.47	1057.60	1057.70	1057.75	1057.74	1057.84	1057.99	1058.07
31	1057.28	---	1057.33	---	1057.52	---	1057.66	1057.73	---	1057.87	---	1058.05
Max	1057.31	1057.36	1057.39	1057.48	1057.53	1057.61	1057.70	1057.75	1057.77	1057.89	1057.99	1058.08
Min	1057.07	1057.12	1057.20	1057.24	1057.37	1057.45	1057.57	1057.64	1057.62	1057.70	1057.79	1057.80

Year 2013 Statistics: Year Max 1,058.08; Year Min 1,057.07

Note: Water level in ft bgs

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report





**Table B-3
Delamar Valley Well 182M-1, Calendar Year 2013
Water-Level Data, Daily Mean Values**



	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	--- ^a	827.11	827.14	827.04	827.21	826.79	827.20	827.07	827.17	827.18	826.95	826.96
2	--- ^a	827.15	827.02	827.08	827.10	826.68	827.18	827.11	827.20	827.13	826.77	826.76
3	--- ^a	827.02	826.87	827.13	826.81	826.76	827.16	827.14	827.25	827.17	826.78	826.63
4	--- ^a	827.05	827.11	827.03	826.79	826.79	827.16	827.13	827.27	827.37	826.88	827.00
5	--- ^a	827.01	827.06	827.01	826.94	826.80	827.18	827.10	827.24	827.32	827.01	826.97
6	--- ^a	827.08	826.95	827.05	826.96	826.83	827.23	827.09	827.23	827.19	826.99	826.97
7	--- ^a	827.06	827.01	826.99	826.85	826.82	827.25	827.13	827.28	827.09	826.83	826.76
8	--- ^a	826.88	826.94	826.83	826.77	826.82	827.25	827.07	827.24	827.02	826.78	827.04
9	--- ^a	827.09	827.21	827.18	826.74	826.85	827.24	827.08	827.18	827.01	826.88	827.12
10	826.89	827.10	827.24	827.17	826.78	826.79	827.15	827.11	827.21	827.24	826.91	826.94
11	827.12	827.17	827.10	826.97	826.80	826.87	827.22	827.07	827.22	827.27	826.91	827.00
12	827.14	827.21	827.10	827.01	826.76	826.86	827.24	827.05	827.19	827.13	826.92	826.94
13	827.14	827.14	827.14	826.93	826.74	826.87	827.25	827.05	827.14	827.07	826.80	827.00
14	827.21	827.15	827.09	826.97	826.68	826.87	827.22	827.04	827.15	827.23	826.69	827.18
15	827.24	827.18	826.98	826.93	826.69	826.85	827.16	827.04	827.20	827.17	826.68	827.08
16	827.16	827.03	826.97	827.13	826.68	826.87	827.19	827.04	827.20	827.21	826.78	827.07
17	827.12	826.88	827.03	827.18	826.73	826.83	827.24	827.03	827.09	827.16	827.00	827.07
18	827.10	827.08	827.10	827.18	826.79	826.72	827.16	827.07	827.18	827.18	827.00	826.97
19	827.13	826.84	827.09	827.02	826.78	826.75	827.12	827.04	827.23	827.12	826.96	826.92
20	827.10	827.03	826.99	827.01	826.79	826.77	827.11	827.01	827.18	827.06	826.94	827.13
21	827.11	827.19	826.99	827.01	826.66	826.77	827.16	827.04	827.16	827.13	827.00	827.16
22	827.11	827.18	827.02	826.97	826.57	826.76	827.22	827.02	827.25	827.08	827.02	827.33
23	827.08	827.02	827.19	827.07	826.79	826.74	827.16	827.02	827.36	827.04	826.98	827.34
24	827.10	827.16	827.08	826.98	826.87	826.86	827.11	827.09	827.22	827.04	827.03	827.24
25	827.07	827.07	827.06	826.97	826.79	826.92	827.13	827.19	827.05	827.04	827.04	827.29
26	826.92	827.11	826.99	827.09	826.81	826.94	827.17	827.23	827.24	827.00	826.95	827.24
27	826.97	827.19	827.06	827.04	826.81	826.96	827.07	827.18	827.36	826.75	826.84	827.19
28	827.12	827.17	827.10	826.91	826.74	826.91	827.05	827.18	827.32	826.74	826.88	827.10
29	827.11	---	827.12	826.89	826.83	826.92	827.13	827.23	827.24	826.97	826.97	827.26
30	827.21	---	827.07	826.88	826.87	826.92	827.23	827.21	827.18	826.98	826.96	827.22
31	827.13	---	827.00	---	826.92	---	827.14	827.19	---	826.98	---	827.17
Max	827.24	827.21	827.24	827.18	827.21	826.96	827.25	827.23	827.36	827.37	827.04	827.34
Min	826.89	826.84	826.87	826.83	826.57	826.68	827.05	827.01	827.05	826.74	826.68	826.63

Year 2013 Statistics: Year Max 827.37; Year Min 826.57

Note: Water level in ft bgs

^aNo data available due to logger malfunction.

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report







**Table B-4
Dry Lake Valley Well 181M-1, Calendar Year 2013
Water-Level Data, Daily Mean Values**

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	675.07	675.06	675.09	674.90	675.11	674.93	674.91	674.94	675.03	675.06	675.18	675.18
2	675.02	675.10	675.01	674.93	675.09	674.79	674.92	674.96	675.05	675.03	675.03	674.98
3	675.06	674.97	674.81	674.95	674.84	674.83	674.88	674.99	675.08	675.07	675.00	674.81
4	675.04	674.99	674.99	674.89	674.76	674.87	674.87	675.00	675.09	675.23	675.07	675.10
5	675.04	674.94	674.96	674.86	674.84	674.90	674.87	674.99	675.07	675.25	675.21	675.07
6	674.91	674.97	674.84	674.89	674.88	674.89	674.88	674.98	675.06	675.15	675.23	675.08
7	675.00	674.98	674.87	674.81	674.89	674.88	674.92	675.00	675.08	675.04	675.11	674.92
8	675.04	674.77	674.79	674.67	674.92	674.85	674.94	674.97	675.03	674.95	675.07	675.15
9	675.00	674.92	674.99	674.96	674.93	674.90	674.96	674.99	675.00	674.92	675.15	675.28
10	674.72	674.96	675.09	674.99	674.98	674.85	674.91	675.02	675.04	675.06	675.19	675.12
11	674.95	675.03	674.98	674.84	675.01	674.89	674.90	675.03	675.07	675.13	675.21	675.19
12	674.98	675.05	674.99	674.86	674.98	674.91	674.93	675.01	675.07	675.04	675.22	675.11
13	674.98	675.01	675.03	674.77	674.93	674.86	674.95	675.03	675.02	675.06	675.13	675.10
14	675.09	675.04	675.00	674.81	674.87	674.91	674.94	675.02	675.02	675.17	675.04	675.27
15	675.14	675.09	674.89	674.73	674.85	674.87	674.89	675.02	675.06	675.14	674.90	675.21
16	675.10	675.00	674.87	674.91	674.84	674.90	674.93	675.03	675.05	675.13	674.96	675.18
17	675.08	674.80	674.90	675.00	674.86	674.89	674.98	675.02	674.97	675.08	675.19	675.16
18	675.06	674.95	674.95	675.02	674.93	674.81	674.96	675.06	675.02	675.14	675.15	674.99
19	675.08	674.72	674.97	674.93	674.93	674.83	674.93	675.04	675.11	675.13	675.03	674.90
20	675.06	674.81	674.86	674.90	674.94	674.85	674.91	675.03	675.04	675.06	674.99	675.06
21	675.06	674.97	674.86	674.90	674.87	674.84	674.93	675.04	674.96	675.15	675.06	675.06
22	675.06	675.00	674.85	674.87	674.72	674.87	674.99	675.05	675.01	675.15	675.13	675.23
23	675.04	674.87	675.00	674.96	674.84	674.81	674.96	675.01	675.15	675.09	675.11	675.26
24	675.04	675.00	674.94	674.89	674.95	674.82	674.95	675.02	675.04	675.11	675.14	675.18
25	675.02	674.97	674.91	674.88	674.86	674.91	674.98	675.08	674.86	675.18	675.20	675.23
26	674.86	674.98	674.85	674.98	674.87	674.94	675.03	675.09	675.01	675.17	675.17	675.20
27	674.88	675.06	674.90	675.00	674.87	674.98	674.96	675.02	675.17	674.92	675.08	675.15
28	674.99	675.06	674.94	674.88	674.80	674.92	674.92	675.05	675.17	674.90	675.09	675.04
29	675.02	---	674.99	674.85	674.84	674.89	674.99	675.09	675.11	675.11	675.17	675.20
30	675.11	---	674.96	674.79	674.87	674.88	675.04	675.09	675.05	675.15	675.17	675.18
31	675.07	---	674.89	---	674.95	---	675.02	675.06	---	675.17	---	675.13
Max	675.14	675.10	675.09	675.02	675.11	674.98	675.04	675.09	675.17	675.25	675.23	675.28
Min	674.72	674.72	674.79	674.67	674.72	674.79	674.87	674.94	674.86	674.90	674.90	674.81

Year 2013 Statistics: Year Max 675.28; Year Min 674.67

Note: Water level in ft bgs

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report





**Table B-5
Dry Lake Valley Well 380531114534201, Calendar Year 2013
Water-Level Data, Daily Mean Values**

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT ^b	NOV ^b	DEC ^b
1	844.84	844.75	844.91	844.48	844.75	844.65	844.55	844.41	844.48	844.48	844.69	844.61
2	844.82	844.79	844.74	844.56	844.93	844.45	844.55	844.40	844.49	844.41	844.48	844.32
3	844.83	844.60	844.38	844.66	844.58	844.44	844.48	844.46	844.54	844.43	844.30	843.98
4	844.78	844.56	844.48	844.56	844.32	844.51	844.42	844.49	844.56	844.71	844.38	844.30
5	844.77	844.45	844.50	844.48	844.32	844.58	844.38	844.47	844.53	844.83	844.63	844.41
6	844.54	844.46	844.34	844.49	844.42	844.57	844.41	844.45	844.50	844.72	844.77	844.45
7	844.58	844.45	844.36	844.36	844.46	844.53	844.50	844.45	844.51	844.50	844.65	844.37
8	844.72	844.16	844.26	844.06	844.57	844.51	844.57	844.42	844.44	844.27	844.48	844.49
9	844.63	844.32	844.53	844.45	844.62	844.52	844.62	844.43	844.35	844.12	844.52	844.76
10	844.24	844.53	844.83	844.66	844.71	844.44	844.55	844.48	--- ^a	844.29	844.60	844.70
11	844.50	844.67	844.76	844.51	844.77	844.51	844.50	844.50	--- ^a	844.52	844.65	844.70
12	844.58	844.81	844.75	844.50	844.71	844.53	844.50	844.49	--- ^a	844.47	844.70	844.60
13	844.62	844.79	844.79	844.33	844.60	844.48	844.52	844.53	--- ^a	844.45	844.55	844.53
14	844.76	844.81	844.73	844.29	844.45	844.51	844.52	844.55	--- ^a	844.63	844.34	844.76
15	844.94	844.89	844.54	844.21	844.39	844.50	844.44	844.56	844.44	844.63	844.05	844.72
16	844.97	844.71	844.40	844.42	844.33	844.55	844.47	844.56	844.47	844.63	844.07	844.66
17	844.89	844.41	844.39	844.71	844.35	844.53	844.58	844.53	844.31	844.53	844.44	844.58
18	844.79	844.45	844.51	844.89	844.50	844.39	844.54	844.58	844.38	844.60	844.53	844.25
19	844.78	844.15	844.59	844.77	844.57	844.36	844.49	844.57	844.52	844.59	844.39	843.98
20	844.73	844.17	844.45	844.68	844.62	844.43	844.43	844.51	844.45	844.47	844.30	844.16
21	844.71	844.54	844.40	844.64	844.45	844.45	844.44	844.52	844.30	844.56	844.38	844.26
22	844.67	844.65	844.39	844.54	844.22	844.49	844.53	844.52	844.28	844.58	844.55	844.59
23	844.63	844.56	844.60	844.64	844.32	844.37	844.55	844.45	844.56	844.50	844.54	844.76
24	844.63	844.69	844.59	844.59	844.52	844.38	844.50	844.46	844.49	844.49	844.57	844.70
25	844.60	844.66	844.55	844.54	844.49	844.54	844.52	844.54	844.20	844.58	844.69	844.74
26	844.34	844.69	844.43	844.71	844.49	844.65	844.59	844.58	844.32	844.63	844.70	844.65
27	844.25	844.84	844.48	844.73	844.48	844.72	844.52	844.50	844.60	844.28	844.50	844.55
28	844.46	844.89	844.57	844.56	844.38	844.66	844.39	844.51	844.71	844.00	844.45	844.35
29	844.58	---	844.69	844.40	844.41	844.57	844.47	844.58	844.64	844.28	844.57	844.50
30	844.77	---	844.66	844.31	844.49	844.52	844.60	844.58	844.53	844.47	844.60	844.52
31	844.78	---	844.52	---	844.65	---	844.56	844.53	---	844.62	---	844.46
Max	844.97	844.89	844.91	844.89	844.93	844.72	844.62	844.58	844.71	844.83	844.77	844.76
Min	844.24	844.15	844.26	844.06	844.22	844.36	844.38	844.40	844.20	844.00	844.05	843.98



Year 2013 Statistics: Year Max: 844.97; Year Min 843.98

Note: Water level in ft bgs

^aMissing data

^bProvisional data provided by the USGS

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report







**Table B-6
Pahrnagat Valley Well 209M-1, Calendar Year 2013
Water-Level Data, Daily Mean Values**

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	1199.98	1199.86	1199.78	1200.02	1199.91	1199.87	1199.98	1199.73	1199.84	1199.61	1200.19	1200.42
2	1199.91	1199.86	1199.73	1199.93	1199.76	1199.91	1199.96	1199.78	1199.87	1199.56	1199.88	1200.18
3	1199.93	1199.86	1199.84	1199.84	1199.76	1199.93	1199.94	1199.78	1199.92	1199.60	1199.82	1199.92
4	1199.92	1199.88	1199.95	1199.84	1199.84	1199.92	1199.95	1199.80	1199.95	1199.81	1199.98	1200.29
5	1199.91	1199.90	1199.92	1199.91	1199.96	1199.88	1199.95	1199.76	1199.89	1199.79	1200.15	1200.72
6	1199.92	1199.96	1199.94	1199.86	1199.98	1199.83	1199.96	1199.81	1199.87	1199.63	1200.25	1200.75
7	1199.92	1199.94	1200.02	1199.97	1199.99	1199.80	1199.94	1199.84	1199.91	1200.05	1199.93	1200.56
8	1199.94	1200.06	1200.04	1200.02	1199.88	1199.81	1199.87	1199.83	1199.86	1199.72	1199.89	1200.87
9	1199.90	1200.10	1200.07	1200.01	1199.91	1200.02	1199.78	1199.80	1199.77	1199.70	1199.91	1201.06
10	1199.95	1200.09	1199.97	1199.94	1199.86	1200.03	1199.78	1199.84	1199.85	1199.90	1199.92	1200.90
11	1200.09	1200.04	1199.92	1199.92	1199.76	1200.06	1199.84	1199.81	1199.95	1200.05	1199.97	1200.85
12	1200.07	1200.04	1199.86	1199.90	1199.75	1200.06	1199.81	1199.83	1199.94	1199.97	1199.99	1200.81
13	1200.09	1199.90	1199.82	1199.96	1199.77	1200.05	1199.80	1199.84	1199.56	1199.94	1199.88	1200.72
14	1200.01	1199.80	1199.83	1200.00	1199.81	1200.04	1199.80	1199.80	1199.62	1200.08	1199.75	1201.00
15	1199.92	1199.74	1199.85	1200.13	1199.91	1200.03	1199.81	1199.80	1199.80	1200.02	1199.52	1200.89
16	1199.87	1199.72	1199.95	1200.04	1199.96	1199.99	1199.83	1199.79	1199.76	1200.03	1199.59	1200.81
17	1199.81	1199.77	1200.01	1200.04	1200.04	1200.00	1199.82	1199.78	1199.58	1199.98	1199.93	1200.76
18	1199.79	1199.83	1200.01	1199.92	1199.95	1200.06	1199.76	1199.81	1199.69	1200.02	1199.98	1200.55
19	1199.74	1199.92	1199.99	1199.86	1199.91	1200.12	1199.76	1199.81	1199.82	1200.03	1199.96	1200.26
20	1199.76	1200.04	1199.99	1199.83	1199.86	1200.09	1199.79	1199.81	1199.74	1199.89	1200.24	1200.51
21	1199.75	1200.04	1200.07	1199.87	1199.85	1200.10	1199.81	1199.78	1199.56	1200.07	1200.33	1200.57
22	1199.79	1200.01	1200.08	1199.88	1199.95	1200.09	1199.79	1199.80	1199.60	1200.03	1200.43	1200.86
23	1199.80	1199.97	1200.03	1199.85	1199.99	1200.13	1199.81	1199.83	1199.86	1199.99	1200.42	1200.94
24	1199.85	1199.96	1200.04	1199.85	1199.93	1200.16	1199.79	1199.86	1199.70	1199.99	1200.51	1200.84
25	1199.83	1199.94	1200.03	1199.91	1199.92	1200.12	1199.78	1199.81	1199.49	1200.05	1200.50	1200.86
26	1199.88	1199.91	1200.06	1199.87	1199.90	1200.08	1199.78	1199.78	1199.59	1200.04	1200.49	1200.76
27	1199.98	1199.92	1200.12	1199.86	1200.06	1199.97	1199.81	1199.80	1199.77	1199.74	1200.30	1200.71
28	1200.05	1199.83	1200.11	1199.82	1200.01	1199.83	1199.84	1199.84	1199.68	1199.58	1200.27	1200.50
29	1200.00	---	1200.05	1199.92	1200.04	1199.84	1199.81	1199.93	1199.66	1199.86	1200.41	1200.69
30	1199.97	---	1200.01	1200.01	1200.02	1199.87	1199.76	1199.93	1199.61	1200.01	1200.50	1200.68
31	1199.91	---	1200.04	---	1199.95	---	1199.71	1199.89	---	1200.18	---	1200.65
Max	1200.09	1200.10	1200.12	1200.13	1200.06	1200.16	1199.98	1199.93	1199.95	1200.18	1200.51	1201.06
Min	1199.74	1199.72	1199.73	1199.82	1199.75	1199.80	1199.71	1199.73	1199.49	1199.56	1199.52	1199.92

Year 2013 Statistics: Year Max 1,201.06; Year Min 1,199.49

Note: Water level in ft bgs

2013 DDC Hydrologic Monitoring, Management, and Mitigation Plan Status and Data Report





This Page Left Intentionally Blank

Appendix C

Periodic Water-Level Measurements and Hydrographs for SNWA Exploratory and Test Wells

**Table C-1
Periodic Water-Level Measurements Collected
at SNWA Exploratory and Test Wells**



Site Number	Station Local Number ^a	Well Depth (ft bgs)	Surface ^b Elevation (ft amsl)	Water Level			
				Date	Depth to Water (ft bgs)	Well Status ^c	Measurement Method ^d
CAV6002X	---	901	5,987.97	1/7/2013	145.26	S	T
				2/11/2013	145.38	S	T
				4/1/2013	145.41	S	T
				5/6/2013	145.39	S	T
				7/8/2013	145.57	S	T
				8/27/2013	145.65	S	T
				11/20/2013	145.77	S	T
CAV6002M2	---	885	5,982.81	1/7/2013	140.26	S	T
				2/11/2013	140.44	S	T
				4/1/2013	140.42	S	T
				5/6/2013	140.45	S	T
				7/8/2013	140.58	S	T
				8/27/2013	140.70	S	T
				11/20/2013	140.81	S	T



^aStation Local Numbers provided by the Nevada Division of Water Resources.

^bElevations are North American Vertical Datum of 1988 (NAVD88).

^cS = Static conditions

^dT = Electric tape measurement







This Page Left Intentionally Blank

Appendix D

Spring Discharge Measurements and Hydrographs

Table D-1
Spring Discharge Measurements
 (Page 1 of 3)

Station Name	Primary Name	Date	Discharge	Unit	Agency
Coyote Spring	1810401	5/20/2013	0.64	GPM	SNWA
		10/15/2013	0.00	GPM	SNWA
Hot Creek Spring near Sunnyside, NV	09415558	1/24/2013	14.9	CFS	USGS
		3/4/2013	14.8	CFS	USGS
		4/10/2013	14.4	CFS	USGS
		6/4/2013	13.8	CFS	USGS
		7/17/2013	13.3	CFS	USGS
		9/10/2013	13.4	CFS	USGS
		10/21/2013	13.3	CFS	USGS
		12/13/2013	14.8	CFS	USGS
Moorman Spring	2071101	4/24/2013	0.32	CFS	USGS
		4/24/2013	0.29	CFS	USGS
		9/25/2013	0.38	CFS	USGS
		9/25/2013	0.39	CFS	USGS
Flag Spring 3	2071301	4/17/2013	1.6	CFS	SNWA
		4/22/2013	1.55	CFS	USGS
		4/22/2013	1.72	CFS	USGS
		5/21/2013	1.6	CFS	SNWA
		6/19/2013	1.7	CFS	SNWA
		7/31/2013	1.7	CFS	SNWA
		9/19/2013	1.6	CFS	SNWA
		9/23/2013	1.55	CFS	USGS
		9/23/2013	2.26	CFS	USGS
		10/17/2013	1.9	CFS	SNWA
Flag Spring 2	2071302	1/16/2013	2.7	CFS	SNWA
		3/6/2013	2.5	CFS	SNWA
		4/17/2013	2.6	CFS	SNWA
		4/22/2013	2.86	CFS	USGS
		4/22/2013	2.66	CFS	USGS
		5/21/2013	2.8	CFS	SNWA
		6/19/2013	2.6	CFS	SNWA
		7/31/2013	2.8	CFS	SNWA
		9/19/2013	2.5	CFS	SNWA
		9/23/2013	2.98	CFS	USGS
		9/23/2013	2.94	CFS	USGS
		10/17/2013	2.6	CFS	SNWA





Table D-1
Spring Discharge Measurements
 (Page 2 of 3)

Station Name	Primary Name	Date	Discharge	Unit	Agency
Flag Spring 1	2071303	4/17/2013	2.2	CFS	SNWA
		4/22/2013	1.95	CFS	USGS
		4/22/2013	1.91	CFS	USGS
		5/21/2013	2.6	CFS	SNWA
		6/19/2013	2.9	CFS	SNWA
		7/31/2013	2.5	CFS	SNWA
		9/19/2013	2.2	CFS	SNWA
		9/23/2013	2.10	CFS	USGS
		9/23/2013	2.07	CFS	USGS
		10/17/2013	2.5	CFS	SNWA
Hardy Springs	2071501	4/17/2013	0.34	CFS	SNWA
		5/21/2013	0.32	CFS	SNWA
		6/19/2013	0.41	CFS	SNWA
		7/31/2013	0.33	CFS	SNWA
		9/19/2013	0.35	CFS	SNWA
		10/16/2013	0.33	CFS	SNWA
Crystal Springs near Hiko, NV	2090401	1/24/2013	12.1	CFS	USGS
		3/4/2013	12.0	CFS	USGS
		4/10/2013	3.01	CFS	USGS
		4/10/2013	3.01	CFS	USGS
		5/30/2013	12.5	CFS	USGS
		7/10/2013	11.6	CFS	USGS
		7/10/2013	12.3	CFS	USGS
		9/6/2013	11.8	CFS	USGS
		10/22/2013	12.1	CFS	USGS
		12/10/2013	12.9	CFS	USGS
Crystal Springs Diversion near Hiko, NV	09415589	1/24/2013	0.00	CFS	USGS
		3/4/2013	0.00	CFS	USGS
		4/10/2013	7.31	CFS	USGS
		4/10/2013	7.31	CFS	USGS
		5/30/2013	0.00	CFS	USGS
		7/10/2013	0.00	CFS	USGS
		9/6/2013	0.00	CFS	USGS
		10/22/2013	0.60	CFS	USGS
		10/22/2013	0.68	CFS	USGS
		12/10/2013	0.00	CFS	USGS
Ash Springs Creek below Diversion at HWY 93 at Ash Springs, NV	09415645	1/22/2013	19.7	CFS	USGS
		1/22/2013	19.5	CFS	USGS
		3/7/2013	18.8	CFS	USGS
		3/7/2013	18.6	CFS	USGS

Table D-1
Spring Discharge Measurements
 (Page 3 of 3)

Station Name	Primary Name	Date	Discharge	Unit	Agency
Ash Springs Creek below Diversion at HWY 93 at Ash Springs, NV (cont.)	09415645	4/10/2013	17.1	CFS	USGS
		4/10/2013	18.6	CFS	USGS
		5/30/2013	19.1	CFS	USGS
		7/10/2013	17.0	CFS	USGS
		7/10/2013	16.8	CFS	USGS
		9/6/2013	16.2	CFS	USGS
		10/22/2013	18.3	CFS	USGS
		12/10/2013	18.2	CFS	USGS
Ash Springs Creek Diversion Ditch below HWY 93 at Ash Springs, NV	094156395	1/22/2013	0.12	CFS	USGS
		3/7/2013	0.019	CFS	USGS
		4/1/2013	0.044	CFS	USGS
		4/1/2013	0.033	CFS	USGS
		4/1/2013	0.026	CFS	USGS
		4/10/2013	0.00	CFS	USGS
		5/30/2013	0.00	CFS	USGS
		7/10/2013	0.00	CFS	USGS
		9/6/2013	0.00	CFS	USGS
		10/22/2013	0.00	CFS	USGS
Cave Spring	1800101	5/21/2013	0.00	CFS	SNWA
		10/15/2013	0.00	CFS	SNWA
Littlefield Spring	1810301	5/20/2013	0.03	CFS	SNWA
		10/15/2013	0.03	CFS	SNWA
Grassy Spring	1820101	5/20/2013	0.00	CFS	SNWA
		10/15/2013	0.00	CFS	SNWA
Silver King Well	381624114540302	5/21/2013	0.90	GPM	SNWA
		10/15/2013	0.00	GPM	SNWA








Table D-2
Discharge Measurement Summary of Flag Springs Complex

Spring Name	Average Discharge ^a (cfs)	Minimum Discharge ^a (cfs)	Maximum Discharge ^a (cfs)	Standard Deviation ^a (cfs)	April 2013 Discharge ^b (cfs)	September 2013 Discharge ^b (cfs)
Flag Spring 1 (North)	2.35	1.54	3.49	0.38	1.93	2.08
Flag Spring 2 (Middle)	2.84	0.50	3.64	0.40	2.76	2.96
Flag Spring 3 (South)	2.12	1.22	3.66	0.44	1.64	1.90

^aPeriod of record (1982-2013).

^b2013 Discharge measurements are the average of two reported measurements.

Source: USGS (2014)




Table D-3
Discharge Measurement Summary of Hardy Springs

Spring Name	Average Discharge ^{a,b} (cfs)	Minimum Discharge ^{a,b} (cfs)	Maximum Discharge ^{a,b} (cfs)	Standard Deviation (cfs)	October 2013 Discharge ^b (cfs)
Hardy Springs	0.34	0.27	0.44	0.04	0.33

^aBased on single measurements in 2004 and 2009 and multiple measurements per year from 2010 through 2013.

^bSource: SNWA data

Table D-4
Annual Discharge at Crystal Springs


Water Year ^{a,b}	Crystal Springs (09415590)		Crystal Springs Diversion (09415589)			Total Combined Discharge (afy)
	Annual Discharge (afy)	Average Annual Discharge (cfs)	Annual Discharge (afy)	Average Annual Discharge (cfs)	Days Diverted	
2005	8,110	11.2	1,230	1.70	78	9,340
2006	8,190	11.3	923	1.28	67	9,113
2007	8,230	11.4	998	1.38	67	9,228
2008	8,100	11.2	1,020	1.40	80	9,120
2009	8,090	11.2	987	1.36	74	9,077
2010	8,120	11.2	743	1.03	52	8,863
2011	7,860	10.9	1,100	1.52	78	8,960
2012	8,160	11.2	710	0.98	50	8,870
2013	7,960	11.0	800 ^d	1.11 ^d	53 ^d	8,760 ^d
Average for the period of record ^c	8,091	11.2	946 ^d	1.31 ^d	67 ^d	9,037 ^d

^aWater years 1990, 1991, 1992, 1993, and 1999 are excluded as explained in the text.

^bData are from USGS Water Resources Data - Nevada water years 2005 through 2013 (USGS, 2014).

^cThese values are extrapolated from the Crystal Springs gaging station records published by USGS (USGS, 2013).

^dThese values for 2013 are based on Preliminary data published by USGS (USGS, 2013).



**Table D-5
Annual Discharge at Ash Springs**

Water Year ^{a,b}	Ash Springs ^c (09415640 and 09415645)		Ash Springs Diversion ^d (09415639 and 094156395)			Total Combined Discharge (afy)
	Annual Discharge (afy)	Average Annual Discharge (cfs)	Annual Discharge (afy)	Average Annual Discharge (cfs)	Days Diverted	
2005	10,080	13.9	2,190	3.03	365	12,270
2006	8,780	12.1	2,810	3.88	365	11,590
2007	11,570	16.0	2,480	3.43	365	14,050
2008	11,740	16.2	2,600	3.58	366	14,340
2009	11,900	16.4	1,860	2.57	365	13,760
2010	12,710	17.6	1,570	2.17	365	14,280
2011	12,260	16.9	1,560	2.16	282	13,820
2012	13,000	17.9	429	0.59	70	13,429
2013 ^f	13,030	18.0	120	0.17	26	13,150
Average for the period of record ^{ef}	11,674	16.1	1,735	2.40	285	13,410

^aData from USGS Water Resources Data-Nevada water years 2005 through 2012 (USGS, 2013).

^bPeriod of record for Ash Springs Diversion (09415639) is December 12, 2003 to July 7, 2011. The 2004 water year is incomplete.

^cMean daily values for new site (09415645) used from July 8, 2011 to present.

^dMean daily values for new site (094156395) used from July 5, 2011 to present.

^eThese values are extrapolated from the Ash Springs gaging station records published by USGS (USGS, 2013).

^fThese values for 2013 are based on Preliminary data published by USGS (USGS, 2013).





Table D-6
Station Number 2090102 - Hiko Spring at Hiko, NV, Water Year 2013
Mean Daily Discharge Values

Day	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.4	5.4	5.5	5.8	6.2	5.6	5.7	0.0	5.9	0.0	5.9	0.0
2	5.7	5.5	5.7	5.8	5.9	5.3	0.0	5.8	5.8	0.0	6.0	0.0
3	5.9	5.7	5.7	5.8	5.4	5.8	0.0	5.3	6.0	6.6	6.0	0.0
4	6.0	5.8	5.6	5.8	5.4	0.0	0.0	5.4	0.0	6.2	6.0	5.5
5	6.0	5.7	5.9	5.8	5.8	0.0	0.0	5.9	7.6	5.8	6.5	5.8
6	6.0	5.2	5.8	5.9	6.2	5.6	0.0	6.0	6.6	5.9	0.0	5.7
7	6.8	5.4	5.9	5.8	6.1	6.1	5.8	6.1	5.7	6.0	0.0	5.9
8	0.0	5.0	5.9	5.8	6.4	5.9	5.3	6.0	0.0	6.0	7.3	6.0
9	0.0	5.5	5.9	5.8	6.1	0.0	5.5	6.1	6.6	5.8	7.3	5.8
10	6.6	5.8	5.9	5.8	5.8	0.0	5.9	7.5	6.1	5.8	6.0	5.8
11	5.6	5.8	5.9	5.8	5.8	0.0	6.1	0.0	5.8	6.5	6.0	5.8
12	5.6	5.8	5.9	5.8	4.9	0.0	6.2	6.1	5.9	0.0	5.8	6.0
13	5.5	5.7	5.9	5.8	5.9	5.5	6.1	6.5	6.1	0.0	5.9	5.9
14	5.0	0.0	5.8	5.8	5.7	5.2	6.4	5.6	6.0	6.2	5.9	5.9
15	5.5	0.0	5.6	5.8	5.4	5.5	0.0	5.8	5.9	6.2	5.9	5.9
16	5.8	0.0	5.8	5.8	5.3	5.8	0.0	5.1	6.6	6.0	5.9	5.9
17	5.9	7.0	5.9	5.8	4.9	5.8	0.0	5.5	0.0	6.0	5.9	5.9
18	5.9	6.0	5.9	5.9	6.2	5.9	0.0	5.8	0.0	5.7	7.1	6.1
19	5.9	5.4	5.9	5.9	6.1	6.1	5.3	6.0	0.0	5.8	7.1	6.3
20	4.9	5.2	5.8	5.9	5.7	6.5	5.2	6.0	6.3	5.8	0.0	6.3
21	3.9	5.6	5.8	5.8	5.8	0.0	4.7	6.1	5.0	5.9	5.9	6.3
22	5.0	5.9	5.8	5.5	5.7	0.0	5.3	7.3	5.0	5.9	5.9	6.3
23	5.4	5.9	5.9	5.3	5.7	0.0	0.0	0.0	4.7	5.3	6.0	6.3
24	5.4	5.9	5.9	5.3	5.6	0.0	5.6	0.0	5.4	7.0	5.9	6.2
25	5.4	5.9	5.8	5.4	6.8	6.1	5.7	0.0	5.7	0.0	5.7	0.0
26	6.0	6.0	5.8	5.8	7.0	5.2	5.8	0.0	5.7	0.0	5.9	0.0
27	7.4	5.8	5.9	5.4	0.0	4.9	7.1	5.5	0.0	6.3	5.9	0.0
28	7.9	6.2	5.7	5.1	5.8	5.4	7.3	5.3	5.6	5.7	5.8	0.0
29	0.0	6.0	5.7	5.4	--	5.5	6.9	5.1	5.9	5.7	5.8	4.4
30	6.3	5.6	5.8	5.2	--	5.6	0.0	5.6	5.9	5.6	6.2	4.9
31	6.0	--	5.8	5.9	--	5.5	--	5.9	--	5.9	7.4	--
Total	163	155	180	176	158	119	112	147	142	150	173	135
Min	0.0	0.0	5.5	5.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Max	7.9	7.0	5.9	6.2	7.0	6.5	7.3	7.5	7.6	7.0	7.4	6.3
Mean	5.25	5.16	5.81	5.69	5.63	3.83	3.73	4.75	4.73	4.83	5.58	4.50
Ac-ft	323	307	356	348	313	236	222	291	281	297	343	267

Note: Values are in cfs unless noted otherwise. e = Estimated day.

LOCATION: UTM NAD 1983 Zone 11N (meters), Northing 4,162,554 m, Easting 656,915 m, in SW1/4 NE1/4 SW1/4 sec.14, T. 4S., R. 60E, Lincoln County, 0.5 mi southwest of the office.

DRAINAGE AREA: Indeterminate.

PERIOD OF RECORD: June 2009 to current year.

GAGE: Ultra-sonic flow meter. Elevation of the gage is 3,868 ft amsl NAVD88.

REMARKS: Records are good except for estimated days which are rated as poor. Discharge records are affected by both upstream and downstream agricultural diversions.

Annual Statistics	
Min:	0.0
Max:	7.9
Annual Total (Acre-ft):	3,584
Annual Mean (cfs):	4.96




Table D-7
Station Number 2071302 - Flag Spring 2 near Sunnyside, NV, Water Year 2013
Mean Daily Discharge Values

Day	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	2.6	2.6	2.6	2.8	2.6	2.5	2.5	2.6	2.8	2.7	2.9	2.6
2	2.6	2.6	2.6	2.8	2.6	2.5	2.5	2.6	2.8	2.7	2.8	2.6
3	2.6	2.6	2.6	2.8	2.6	2.5	2.5	2.6	2.8	2.7	2.8	2.6
4	2.6	2.6	2.6	2.8	2.6	2.5	2.6	2.7	2.8	2.7	2.8	2.6
5	2.6	2.6	2.6	2.8	2.6	2.5	2.6	2.7	2.8	2.7	2.8	2.6
6	2.6	2.6	2.6	2.9	2.6	2.5	2.6	2.7	2.8	2.7	2.8	2.5
7	2.6	2.6	2.6	2.9	2.6	2.4	2.6	2.7	2.8	2.8	2.8	2.5
8	2.6	2.6	2.6	2.9	2.6	2.4	2.6	2.7	2.7	2.8	2.8	2.5
9	2.6	2.6	2.6	2.9	2.6	2.4	2.6	2.7	2.7	2.8	2.8	2.5
10	2.6	2.5	2.7	2.9	2.6	2.4	2.6	2.7	2.8	2.8	2.8	2.5
11	2.6	2.6	2.7	2.9	2.6	2.4	2.6	2.7	2.8	2.8	2.8	2.5
12	2.6	2.6	2.7	2.9	2.6	2.4	2.6	2.7	2.8	2.8	2.8	2.5
13	2.6	2.6	2.7	2.9	2.6	2.5	2.6	2.7	2.7	2.8	2.7	2.5
14	2.6	2.6	2.7	2.9	2.6	2.5	2.6	2.7	2.7	2.8	2.7	2.5
15	2.6	2.6	2.7	2.9	2.6	2.5	2.6	2.8	2.7	2.8	2.7	2.5
16	2.6	2.6	2.7	2.8	2.6	2.5	2.6	2.8	2.7	2.8	2.7	2.5
17	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.7	2.8	2.7	2.5
18	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.7	2.8	2.7	2.5
19	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.7	2.8	2.7	2.4
20	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.6	2.8	2.7	2.4
21	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.6	2.8	2.7	2.4
22	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.6	2.8	2.7	2.4
23	2.6	2.5	2.7	2.7	2.6	2.5	2.5	2.8	2.7	2.9	2.7	2.4
24	2.6	2.5	2.8	2.7	2.6	2.5	2.5	2.8	2.7	2.9	2.7	2.5
25	2.6	2.5	2.8	2.7	2.5	2.5	2.6	2.8	2.7	2.9	2.6	2.5
26	2.6	2.5	2.8	2.7	2.5	2.5	2.6	2.8	2.7	2.9	2.6	2.5
27	2.6	2.5	2.8	2.7	2.5	2.5	2.6	2.8	2.7	2.9	2.6	2.5
28	2.6	2.6	2.8	2.7	2.5	2.5	2.6	2.8	2.7	2.9	2.6	2.5
29	2.6	2.6	2.8	2.7	--	2.5	2.6	2.8	2.7	2.9	2.6	2.5
30	2.6	2.6	2.8	2.7	--	2.5	2.6	2.8	2.7	2.9	2.6	2.5
31	2.6	--	2.8	2.6	--	2.5	--	2.8	--	2.9	2.6	--
Total	81	77	84	86	72	77	77	85	82	87	84	75
Min	2.6	2.5	2.6	2.6	2.5	2.4	2.5	2.6	2.6	2.7	2.6	2.4
Max	2.6	2.6	2.8	2.9	2.6	2.5	2.6	2.8	2.8	2.9	2.9	2.6
Mean	2.60	2.56	2.70	2.78	2.59	2.48	2.56	2.75	2.72	2.81	2.72	2.50
Ac-ft	160	152	166	170	143	152	152	168	162	172	166	148

Note: Values are in cfs unless noted otherwise.

LOCATION: UTM NAD 1983 Zone 11N (meters), Northing 4,254,570 m, Easting 672,576 m, in SW1/4 SW1/4 NW1/4 sec. 33 T. 7N., R. 62E., Nye County.


DRAINAGE AREA: Indeterminate.

PERIOD OF RECORD: November 2009 to current year.

GAGE: Bubbler/Pressure sensor. Elevation of the gage is estimated at 5,285 ft amsl NAVD88.

REMARKS: Records are rated as good.

Annual Statistics	
Min:	2.4
Max:	2.9
Annual Total (Acre-ft):	1,911
Annual Mean (cfs):	2.65



References

U.S. Geological Survey, 2013, National water information system (NWIS Web), [Internet], [accessed February 2014], available from <http://waterdata.usgs.gov/nwis>.

USGS, see U.S. Geological Survey.



This Page Left Intentionally Blank

Appendix E
2013 DDC Springs Site Photos

E.1.0 INTRODUCTION

This appendix presents photos taken during the biannual field visits to document DDC spring conditions. Many of the DDC springs are controlled by collector systems and have been modified from their natural condition. Others, such as Littlefield and Cave Springs, remain in their natural condition.



Figure E-1
Maynard Spring, May 2013



Figure E-2
Maynard Spring, October 2013



Figure E-3
Cave Spring, May 2013



Figure E-4
Cave Spring, October 2013



Figure E-5
Parker Station, May 2013



Figure E-6
Parker Station, October 2013



Figure E-7
Parker Station Flume, October 2013



Figure E-8
Lewis Well, May 2013



Figure E-9
Lewis Well, October 2013



Figure E-10
Lewis Well Spring Collector Line Access Discharge, October 2013



Figure E-11
Silver King Well, May 2013



Figure E-12
Silver King Well, October 2013



Figure E-13
Coyote Spring, May 2013



Figure E-14
Coyote Spring, October 2013



Figure E-15
Big Mud Spring, May 2013



Figure E-16
Big Mud Spring, October 2013



Figure E-17
Littlefield Spring, May 2013



Figure E-18
Littlefield Spring, October 2013



Figure E-19
Grassy Spring, May 2013



Figure E-20
Grassy Spring, October 2013

Appendix F

Regional and High-Altitude Precipitation-Station Data

Table F-1
2013 Regional Precipitation Data
 (Page 1 of 3)

Blue Eagle Ranch Hanks (RP1730201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.76	0.10	0.82	0.07	0.20	0.00	0.30	0.23	1.53	0.28	1.38	0.80	6.47
Period of Record Statistics (1978 to Present)													
Mean	0.69	0.68	0.86	0.89	0.91	0.39	0.52	0.71	0.70	0.91	0.71	0.49	8.46
Min	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	4.41
Max	1.66	1.97	2.43	2.93	3.43	1.52	2.94	3.92	3.95	4.23	2.53	1.54	15.11
No. Yrs.	34	34	35	35	35	36	36	36	35	35	34	35	29
McGill (RP1790202)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.59	1.05	0.10	0.71	0.35	0.00	0.12	0.75	2.03	1.03	0.50	1.30	8.53
Period of Record Statistics (1892 to Present)													
Mean	0.63	0.66	0.75	0.95	1.02	0.75	0.68	0.76	0.70	0.80	0.56	0.61	8.87
Min	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.76
Max	4.58	2.38	2.54	3.19	3.33	4.30	3.03	3.25	5.57	3.38	1.90	3.05	16.21
No. Yrs.	104	105	106	107	105	105	105	104	104	102	105	106	92
Spring Valley State Park (RP2010201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.00z	0.00z	0.00	0.22	0.06	0.00	1.15	0.44	0.19	0.00	0.00	0.00	2.06
Period of Record Statistics (1974 to Present)													
Mean	0.87	1.21	1.28	0.90	1.04	0.41	0.89	1.26	1.20	1.17	0.64	0.80	11.67
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	5.05
Max	3.81	3.65	4.30	3.92	3.70	2.14	3.68	5.41	9.72	4.95	3.43	6.62	23.48
No. Yrs.	34	34	37	36	37	38	37	39	38	37	36	35	21
Pioche (RP2020201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.90	0.56	1.05	0.00	1.11	0.00	0.95	2.80	3.69	0.52	0.86	1.01	13.45
Period of Record Statistics (1888 to Present)													
Mean	1.54	1.47	1.59	1.03	0.97	0.38	1.00	1.37	0.95	1.02	1.00	1.30	13.62
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.81
Max	6.74	6.02	5.22	4.63	4.30	2.75	4.99	5.01	3.87	3.78	4.79	7.88	27.29
No. Yrs.	77	81	78	81	80	76	78	78	78	77	77	76	65
Caliente (RP2050201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.82	0.94	0.65	0.30	0.98	0.00	1.90	0.40	1.42	0.29	0.81	0.40	8.91
Period of Record Statistics (1903 to Present)													
Mean	0.82	0.94	1.01	0.69	0.54	0.32	0.80	0.89	0.62	0.79	0.68	0.65	8.75
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.84
Max	3.47	3.98	4.59	3.71	2.27	1.95	5.36	4.18	3.14	5.12	3.38	3.76	18.73
No. Yrs.	88	89	86	89	88	88	88	90	91	88	89	89	68



Table F-1
2013 Regional Precipitation Data
 (Page 2 of 3)

Elgin (RP2050202)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00
Period of Record Statistics (1951 to 2012)													
Mean	1.48	1.96	1.42	0.94	0.40	0.27	0.76	0.66	0.61	0.75	0.83	0.84	10.92
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.71
Max	6.47	8.01	6.28	3.09	1.47	1.16	6.06	2.58	3.22	2.89	4.30	3.28	18.43
No. Yrs.	25	27	27	28	28	25	25	27	27	25	25	23	17
Sunnyside (RP2070201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.32	0.40	0.61	0.00	0.54	0.00	0.30	0.65	0.11	0.65	0.00	0.00	3.58
Period of Record Statistics (1891 to Present)													
Mean	0.67	0.79	0.97	0.78	0.80	0.47	0.74	0.81	0.82	0.91	0.55	0.63	8.94
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.58
Max	2.64	3.55	4.82	2.81	3.23	2.79	4.37	3.89	3.69	3.76	4.19	2.80	17.11
No. Yrs.	52	52	53	53	52	53	56	53	51	50	49	45	29
Lund (RP2070202)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.68	0.49	0.19	0.18	0.14	0.00	0.24	0.15	2.46	0.58	1.03	0.74	6.88
Period of Record Statistics (1957 to Present)													
Mean	0.77	0.85	0.99	0.96	0.94	0.80	0.68	0.86	0.80	0.92	0.69	0.73	9.99
Min	0.01	0.00	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	4.99
Max	2.78	2.22	3.44	3.44	3.45	5.37	3.05	4.58	5.01	3.66	2.62	2.91	18.83
No. Yrs.	55	55	54	56	56	56	55	55	56	55	56	55	46
Hiko (RP2090201)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.36	0.03	0.66	0.03	0.49	0.00	0.92	0.32	2.89	0.33	0.82	0.26a	7.11
Period of Record Statistics (1989 to Present)													
Mean	0.74	1.13	0.77	0.52	0.37	0.31	0.47	0.47	0.51	0.53	0.43	0.81	7.16
Min	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.45
Max	2.94	4.13	4.45	1.56	1.69	1.66	1.65	2.52	2.89	3.38	1.91	4.02	13.63
No. Yrs.	22	23	24	23	24	24	24	24	25	24	25	25	20
Paharanagat Wildlife Refuge (RP2090202)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	0.00	0.00t	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00z	0.00
Period of Record Statistics (1964 to Present)													
Mean	0.70	0.75	0.73	0.61	0.37	0.19	0.46	0.58	0.35	0.52	0.49	0.39	6.14
Min	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.23
Max	3.21	3.22	3.03	4.04	1.59	1.20	4.22	3.60	2.30	3.18	2.48	1.74	11.54
No. Yrs.	42	44	46	43	43	47	46	44	48	45	44	42	29

Table F-1
2013 Regional Precipitation Data
 (Page 3 of 3)

Ward Mountain (RP2070301)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
2013	1.40	1.40	0.50	1.10	1.00	0.10	0.70	1.50	6.50	2.00	1.40	1.70	19.30
Period of Record Statistics (1978 to Present)													
Mean	2.52	2.79	2.72	2.43	2.36	0.91	0.99	1.39	1.62	2.02	1.81	2.22	23.78
Min	0.00	0.40	0.30	0.00	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	12.80
Max	6.10	9.50	8.10	5.70	7.00	3.90	4.80	4.70	7.90	6.60	7.20	10.70	39.70
No. Yrs.	33	33	33	33	32	32	32	32	32	36	35	34	32

Note: a = 1 day missing, b = 2 days missing, c = 3 days missing, etc..., z = 26 or more days missing; Long-term means based on summation of period of record monthly mean row values.



**Table F-2
2013 High-Altitude Precipitation Data**

Source	Station Number	Station Name	2013 Precipitation (in.)	Period of Record Statistics				
				Time Period	Mean	Min	Max	No. Yrs.
NDWR	RP1830101	Mount Wilson (NDWR)	16.10	1954 - 2013	16.62	7.50	28.30	57
USGS	RP1840401	Mount Washington	20.50	1984 - 2013	26.31	12.00	62.00	29
USGS	RP1840402	Cave Mountain	19.50	1984 - 2013	20.36	12.00	32.16	30
USGS	RP2030401	Highland Peak	18.75	2001 - 2013	15.63	0.00	28.00	13
USGS	RP2090401	Mt. Irish	9.75	2001 - 2013	7.69	0.00	17.25	13
USGS	RP1830401	Mount Wilson (USGS)	17.75	1983 - 2013	19.00	0.00	47.00	31
USGS	RP1730401	Quinn Canyon Range	16.25	2003 - 2013	13.14	1.75	23.25	11
USGS	RP1820401	Unnamed peak S. of Chokecherry Peak	13.50	2001 - 2013	9.31	0.00	22.50	13
USGS	RP1820402	Unnamed peak in S. Delamar Mtns	15.50	2001 - 2013	11.37	0.00	32.50	13



SOUTHERN NEVADA WATER AUTHORITY

100 City Parkway, Suite 700 • Las Vegas, NV 89106
MAILING ADDRESS: P.O. Box 99956 • Las Vegas, NV 89193-9956
(702) 862-3400 • snwa.com

March 27, 2014

Jason King, P.E., State Engineer
Nevada Division of Water Resources
901 S. Stewart Street, Suite 2002
Carson City, NV 89701

Rosemary Thomas, Ely District Manager
Bureau of Land Management
702 N. Industrial Way
HC 33 Box 3350
Ely, NV 89301

Zane L. Marshall, Director
Water & Environmental Resources
Southern Nevada Water Authority
P.O. Box 99956
Las Vegas, NV 89193-9956

Cathy Wilson, Area Director
Bureau of Indian Affairs, Western Region
2600 N. Central Ave., MS#460
Phoenix, AZ 85004

Bill Hansen, Chief Water Rights Branch
National Park Service, WRD
1201 Oak Ridge Drive, Suite 250
Ft. Collins, CO 80525

Ted Koch, Nevada State Supervisor
U.S. Fish and Wildlife Service
1340 Financial Blvd., Suite 234
Reno, NV 89502

William Dunkelberger, Forest Supervisor
U.S. Forest Service
1200 Franklin Way
Sparks, NV 89431

Dear Mr. King and Stipulation Executive Committee Members:

**SUBJECT: SUBMITTAL OF THE 2013 DDC AND SPRING VALLEY
HYDROLOGIC MONITORING, MANAGEMENT AND MITIGATION
PLAN STATUS AND DATA REPORTS**

The Southern Nevada Water Authority (SNWA) hereby submits the subject reports to the Nevada State Engineer (NSE) and Stipulation Executive Committee (EC). These reports are submitted in satisfaction of reporting requirements set forth in hydrologic monitoring plans approved by the NSE associated with Rulings 6164 through 6167, and Exhibit A of the Stipulations for Withdrawal of Protests for Spring Valley and Dry Lake, Delamar, and Cave (DDC) valleys.

These reports provide the NSE, EC, and Technical Review Panel (TRP) with hydrologic data for calendar year 2013 and a status update of monitoring activities performed by SNWA.

SNWA MEMBER AGENCIES

Big Bend Water District • Boulder City • Clark County Water Reclamation District • City of Henderson • City of Las Vegas • City of North Las Vegas • Las Vegas Valley Water District

Mr. Jason King and
Stipulation Executive Committee Members
March 27, 2014
Page 2

An electronic copy of the data has been submitted to the NSE in the required format. Copies of the reports and NSE electronic data submittal have also been posted on the Spring Valley and DDC valleys data-exchange website.

If you have any questions regarding these reports, please contact James Prieur at (702) 862-7437.

Sincerely,



Zane L. Marshall
Director, Water & Environmental Resources

Enc.

ZLM:dl

c: Rick Felling, Nevada Division of Water Resources
Dan Netcher, Bureau of Land Management
Sarah Peterson, Bureau of Land Management
Ray Roessel, Bureau of Indian Affairs, Western Region
William Van Liew, National Park Service, WRD
Sue Braumiller, U.S. Fish and Wildlife Service
Michael Senn, U.S. Fish and Wildlife Service
Joe Gurrieri, U.S. Forest Service
Gary Karst, National Park Service
Jose Noriega, U.S. Forest Service
Andrew Burns, Southern Nevada Water Authority
James Prieur, Southern Nevada Water Authority