WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 70677
Permit No.
Basin 179

NOTICE OF INTENT NO. 30377

1. OWNER Joseph R. & JoLene Christensen
MAILING ADDRESS Po Box 62 Ely NV 89301
ADDRESS AT WELL LOCATION Lot 9B

2. LOCATION SW ¼ SE ¼ Sec. 12 T. 15 N/S R. 63 E. White Pine County
PERMIT NO. N/A Issued by Water Resources
012-770-50 Parcel No.
None Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[X] Cable [ ] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	1	
Cemented gravel and		1		
Cobbles			172	
gravel clay		172	178	
Cemented gravel cobbles		178	200	
2 gpm at	water	200		
Cemented gravel		200	225	
Lime Stone	water	225	230	
Cemented gravel		230	255	
Lime Stone gravel	water	255	260	
Cemented gravel		260	290	
Lime Stone gravel	water	290	295	
cemented gravel		295	304	

Date started Nov 28, 1997
Date completed Jan 22, 1998

7. WELL TEST DATA
TEST METHOD: [X] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25	52	

8. WELL CONSTRUCTION
Depth Drilled 304 Feet Depth Cased 304 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 Inches		50 Feet	265 Feet
6 Inches		265 Feet	304 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.9	.188	-1	265
5		.188	262	304

Perforations:
Type perforation mill
Size perforation 5 x 2.5" x 6 row
From feet to feet
From 225 feet to 304 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 265 feet

9. WATER LEVEL
Static water level 198 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Nathan R Maynard Contractor
Address Po Box 176 Lund NV 89317 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0022869
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1556
Signed Owen Maynard By driller performing actual drilling on site or contractor
Date Jan 22 1998

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627