

93222

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5625  
 DEC 22 1960  
 Well No. \_\_\_\_\_  
 Permit No. 19788  
 Do not fill in

Owner Thompson Company Driller Paul Free  
 Address 1001 E. 2nd St. Reno Address 1001 E. 2nd St. Reno Lic. No. 30  
 Location of well: N.E. 1/4, S.E. 1/4, Sec. 26, T. 2 N/S, R. 47 E, in Washoe County  
 or Humboldt Ranch  
 Water will be used for irrigation Total depth of well 115'  
 Size of drilled hole 14" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing \_\_\_\_\_ Temp. of water \_\_\_\_\_  
 Diameter and length of casing 14" 115'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 39'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 2/1/60 Date of completion of well 2/15/60  
 Type of well rig Case 115' rig

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	sandy clay
30	75	45	clay
75	81	6	gravel
81	90	9	sand
90	101	11	gravel
101	103	2	clay
103	107	4	gravel
107	115	8	clay - Panola bed

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 75 to 101 ft.

Other aquifers \_\_\_\_\_

---

First water at 36 feet.

Casing perforated

from 36 to 116 ft.

Size of perforations

1/8 x 2 1/2"

