

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. <u>52900</u>
Rec. <u>19</u>
Well No. _____
Permit No. _____

Do not fill in

Owner Jim Moss Driller S.H. McKinney & Sons, Inc.

Address General Delivery, Indian Springs, Nevada Address 1010 South Lic. No. 45

Location of well: $\frac{1}{4}$ Sec. 8, T. $\frac{1}{2}$ N/S, R. $\frac{5}{2}$ E, in Clark County

or Indian Springs

Water will be used for Domestic Use Total depth of well 120'

Size of drilled hole 12" to 50', 10" to 120' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" ID from 0 to 120'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 47 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 6/11/62 Date of completion of well 6/14/62

Type of well rig Bucyrus Erie 24 L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	35	35	clay & gravel	
35	39	4	cement gravel	
39	50	11	clay & gravel	
50	52	2	clay	
52	60	8	clay & gravel (water)	Chief aquifer (water-bearing formation) from <u>70</u> to <u>120</u> ft.
60	70	10	cement gravel (water)	Other aquifers <u>60 to 70'</u>
70	120	50	cement gravel (water)	<u>52 to 60'</u>
				First water at <u>52</u> feet.
				Casing perforated from <u>60</u> to <u>120</u> ft.
				Size of perforations <u>3/16" x 10"</u>

